

# Road

## Model 370

| Sizes                                      | 19    | 21   | 23                   | 25   |
|--------------------------------------------|-------|------|----------------------|------|
| 1. Stand-over height                       |       |      |                      |      |
| Inches                                     | 29.4  | 31.3 | 33.2                 | 35.2 |
| Centimeters                                | 74.7  | 79.5 | 84.4                 | 89.3 |
| 2. Top tube                                |       |      |                      |      |
| Inches                                     | 20.9  | 21.6 | 22.4                 | 23.2 |
| Centimeters                                | 53.0  | 55.0 | 57.0                 | 59.0 |
| 3. Stem extension (standard type, 0° rise) |       |      |                      |      |
| Millimeters                                | 100   | 100  | 100                  | 100  |
| 4. Reach (top tube + stem reach)           |       |      |                      |      |
| Inches                                     | 24.8  | 25.6 | 26.4                 | 27.2 |
| Centimeters                                | 63.0  | 65.0 | 67.0                 | 69.0 |
| 5. Handlebar width (25.4 mm diameter)      |       |      |                      |      |
| Millimeters                                | 390   | 410  | 430                  | 430  |
| 6. Crank arm length                        |       |      |                      |      |
| Millimeters                                | 170   | 170  | 170                  | 170  |
| 7. Steerer length, threaded                |       |      |                      |      |
| Inches                                     | 4.9   | 5.7  | 7.7                  | 9.6  |
| Millimeters                                | 125   | 145  | 195                  | 245  |
| 8. Head tube length                        |       |      |                      |      |
| Inches                                     | 3.3   | 4.1  | 6.1                  | 8.1  |
| Millimeters                                | 85    | 105  | 155                  | 205  |
| 9. Seatpost length (26.2 mm diameter)      |       |      |                      |      |
| Millimeters                                | 220   | 220  | 220                  | 220  |
| 10. Gearing                                | 40/52 |      | 12-14-16-18-21-24-28 |      |

### General Information

|                  |                 |
|------------------|-----------------|
| Hubset, Type     | HyperGlide      |
| Spoke number     | 36              |
| Spokes, Front    | 296 14 ga.      |
| Rear(D/ND)       | 294/296 14 ga.  |
| Tire Size        | 700 x 25        |
| Front Derailleur | 28.6/1 1/8"     |
| Bottom bracket   | BB-CS10         |
| Shell Width      | 68              |
| Axle length      | 122.5           |
| R. dropout width | 126             |
| Headset size     | 22.2/30.0/27.0  |
| Weight           | 25.8 lb/11.7kg. |

### Upgrades

- 14 speed SIS shifting
- Great all round performance
- Trek engineered geometry and fit
- Cartridge bottom bracket
- Double butted Cro-Moly main tubes
- 400 LX rear derailleur

## Model 520

| Sizes                                      | 17       | 19   | 21   | 23                   |
|--------------------------------------------|----------|------|------|----------------------|
| 1. Stand-over height                       |          |      |      |                      |
| Inches                                     | 28.5     | 30.0 | 31.7 | 33.6                 |
| Centimeters                                | 72.4     | 76.3 | 80.5 | 85.3                 |
| 2. Top tube                                |          |      |      |                      |
| Inches                                     | 21.3     | 21.9 | 22.2 | 22.6                 |
| Centimeters                                | 54.0     | 55.5 | 56.5 | 57.5                 |
| 3. Stem extension (standard type, 0° rise) |          |      |      |                      |
| Millimeters                                | 80       | 100  | 100  | 120                  |
| 4. Reach (top tube + stem reach)           |          |      |      |                      |
| Inches                                     | 24.3     | 25.6 | 26.0 | 27.2                 |
| Centimeters                                | 61.7     | 65.0 | 66.0 | 69.0                 |
| 5. Handlebar width (25.4 mm diameter)      |          |      |      |                      |
| Millimeters                                | 410      | 410  | 410  | 430                  |
| 6. Crank arm length                        |          |      |      |                      |
| Millimeters                                | 170      | 175  | 175  | 175                  |
| 7. Steerer length, threaded                |          |      |      |                      |
| Inches                                     | 5.1      | 5.1  | 6.0  | 8.0                  |
| Millimeters                                | 130      | 130  | 153  | 204                  |
| 8. Head tube length                        |          |      |      |                      |
| Inches                                     | 3.7      | 3.7  | 4.6  | 6.6                  |
| Millimeters                                | 93       | 93   | 116  | 167                  |
| 9. Seatpost length (26.8 mm diameter)      |          |      |      |                      |
| Millimeters                                | 250      | 250  | 250  | 250                  |
| 10. Gearing                                | 30/40/50 |      |      | 12-14-16-18-21-24-28 |

### General Information

|                  |                  |
|------------------|------------------|
| Hubset, Type     | HyperGlide       |
| Spoke number     | 36               |
| Spokes, Front    | 297 14 ga.       |
| Rear(D/ND)       | 295/296 14 ga.   |
| Tire Size        | 700 x 28         |
| Front Derailleur | 28.6/1 1/8"      |
| Bottom bracket   | BB-UN51          |
| Shell Width      | 68               |
| Axle length      | 122.5            |
| R. dropout width | 135              |
| Headset size     | 22.2/30.2/26.4   |
| Weight           | 26.6 lb/12.1 kg. |

### Upgrades

- Cross country style touring bike with all the braze-ons
- 21 speed wide ratio gearing with bar end shifters
- Long wheelbase for stability and comfort
- 0° stem and Gel Lite saddle for comfort
- Shimano Deore DX group



## Model 1100

| Sizes                                      | 47       | 52                   | 54   | 56   | 58   | 60   | 62   |
|--------------------------------------------|----------|----------------------|------|------|------|------|------|
| 1. Stand-over height                       |          |                      |      |      |      |      |      |
| Inches                                     | 28.5     | 30.4                 | 31.2 | 31.9 | 32.6 | 33.4 | 33.8 |
| Centimeters                                | 72.4     | 77.1                 | 79.2 | 81.1 | 82.9 | 84.8 | 85.8 |
| 2. Top tube                                |          |                      |      |      |      |      |      |
| Inches                                     | 20.1     | 20.9                 | 21.7 | 21.7 | 22.4 | 22.4 | 23.0 |
| Centimeters                                | 51.0     | 53.0                 | 55.0 | 55.0 | 57.0 | 57.0 | 58.5 |
| 3. Stem extension (standard type, 0° rise) |          |                      |      |      |      |      |      |
| Millimeters                                | 80       | 100                  | 100  | 100  | 120  | 120  | 120  |
| 4. Reach (top tube + stem reach)           |          |                      |      |      |      |      |      |
| Inches                                     | 23.1     | 24.6                 | 25.4 | 25.4 | 27.0 | 27.0 | 27.6 |
| Centimeters                                | 58.6     | 62.6                 | 64.6 | 64.6 | 68.5 | 68.5 | 70.0 |
| 5. Handlebar width (25.4 mm diameter)      |          |                      |      |      |      |      |      |
| Millimeters                                | 390      | 410                  | 410  | 410  | 430  | 430  | 430  |
| 6. Crank arm length                        |          |                      |      |      |      |      |      |
| Millimeters                                | 170      | 170                  | 170  | 170  | 175  | 175  | 175  |
| 7. Steerer length, threaded                |          |                      |      |      |      |      |      |
| Inches                                     | 5.0      | 5.7                  | 6.5  | 7.3  | 8.0  | 8.8  | 9.2  |
| Millimeters                                | 126      | 145                  | 165  | 185  | 204  | 224  | 233  |
| 8. Head tube length                        |          |                      |      |      |      |      |      |
| Inches                                     | 3.4      | 4.1                  | 4.9  | 5.7  | 6.5  | 7.2  | 7.6  |
| Millimeters                                | 86       | 104                  | 124  | 145  | 165  | 183  | 193  |
| 9. Seatpost length (27.2 mm diameter)      |          |                      |      |      |      |      |      |
| Millimeters                                | 250      | 250                  | 250  | 250  | 250  | 250  | 250  |
| 10. Gearing                                | 30/42/52 | 12-14-16-18-21-24-28 |      |      |      |      |      |

### General Information

|                  |                                           |
|------------------|-------------------------------------------|
| Hubset, Type     | HyperGlide                                |
| Spoke number     | 32                                        |
| Spokes, Front    | 299 14 ga.                                |
| Rear(D/ND)       | 296/298 14 ga.                            |
| Tire Size        | 700 x 25                                  |
| Front Derailleur | 34.9 mm/ 1 <sup>3</sup> / <sub>8</sub> in |
| Bottom bracket   | BB-UN51                                   |
| Shell Width      | 68                                        |
| Axle length      | 127.5                                     |
| R. dropout width | 128                                       |
| Headset size     | 22.2/30.2/26.4                            |
| Weight           | 23.0 lb/10.5 kg.                          |

### Upgrades

- Double butted aluminum tubing is light and comfortable
- Easy pedalling with wide range 21 speed gearing
- Gel Lite saddle and 0° stem make long miles comfortable
- Titan Tech rims and IsoTech 3 tires are light, yet durable

## Model 1420

| Sizes                                      | 47       | 50                   | 52   | 54   | 56   | 58   | 60   | 62   |
|--------------------------------------------|----------|----------------------|------|------|------|------|------|------|
| 1. Stand-over height                       |          |                      |      |      |      |      |      |      |
| Inches                                     | 28.5     | 29.6                 | 30.4 | 31.2 | 31.9 | 32.6 | 33.4 | 33.8 |
| Centimeters                                | 72.4     | 75.3                 | 77.1 | 79.2 | 81.1 | 82.9 | 84.8 | 85.8 |
| 2. Top tube                                |          |                      |      |      |      |      |      |      |
| Inches                                     | 20.1     | 20.9                 | 20.9 | 21.7 | 21.7 | 22.4 | 22.4 | 23.0 |
| Centimeters                                | 51.0     | 53.0                 | 53.0 | 55.0 | 55.0 | 57.0 | 57.0 | 58.5 |
| 3. Stem extension (standard type, 0° rise) |          |                      |      |      |      |      |      |      |
| Millimeters                                | 80       | 80                   | 100  | 100  | 100  | 120  | 120  | 120  |
| 4. Reach (top tube + stem reach)           |          |                      |      |      |      |      |      |      |
| Inches                                     | 23.1     | 23.9                 | 24.6 | 25.4 | 25.4 | 27.0 | 27.0 | 27.6 |
| Centimeters                                | 58.6     | 60.6                 | 62.6 | 64.6 | 64.6 | 68.5 | 68.5 | 70.0 |
| 5. Handlebar width (25.4 mm diameter)      |          |                      |      |      |      |      |      |      |
| Millimeters                                | 390      | 390                  | 410  | 410  | 410  | 430  | 430  | 430  |
| 6. Crank arm length                        |          |                      |      |      |      |      |      |      |
| Millimeters                                | 170      | 170                  | 170  | 170  | 170  | 175  | 175  | 175  |
| 7. Steerer length, threaded                |          |                      |      |      |      |      |      |      |
| Inches                                     | 4.7      | 4.7                  | 5.5  | 6.2  | 7.0  | 7.8  | 8.6  | 8.9  |
| Millimeters                                | 119      | 119                  | 138  | 158  | 178  | 197  | 217  | 226  |
| 8. Head tube length                        |          |                      |      |      |      |      |      |      |
| Inches                                     | 3.4      | 3.4                  | 4.1  | 4.9  | 5.7  | 6.5  | 7.2  | 7.6  |
| Millimeters                                | 86       | 86                   | 104  | 124  | 145  | 165  | 183  | 193  |
| 9. Seatpost length (27.2 mm diameter)      |          |                      |      |      |      |      |      |      |
| Millimeters                                | 250      | 250                  | 250  | 250  | 250  | 250  | 250  | 250  |
| 10. Gearing                                | 30/42/52 | 12-14-16-18-21-24-28 |      |      |      |      |      |      |

### General Information

|                  |                                           |
|------------------|-------------------------------------------|
| Hubset, Type     | HyperGlide                                |
| Spoke number     | 32                                        |
| Spokes, Front    | 299 14 ga.                                |
| Rear(D/ND)       | 296/298 14 ga.                            |
| Tire Size        | 700 x 25                                  |
| Front Derailleur | 34.9 mm/ 1 <sup>3</sup> / <sub>8</sub> in |
| Bottom bracket   | BB-UN51                                   |
| Shell Width      | 68                                        |
| Axle length      | 127.5                                     |
| R. dropout width | 128                                       |
| Headset size     | 22.2/30.2/26.4                            |
| Weight           | 23.3 lb/10.6 kg.                          |

### Upgrades

- Bar end shifters
- Look PM166 ARC pedals
- Trek epoxy bonded aluminum fork
- Shimano Deore DX derailleurs
- 0° stem and Gel Lite saddle for comfort



## Model 1200

| Sizes                                       | 47    | 52   | 54                   | 56   | 58   | 60   | 62   |
|---------------------------------------------|-------|------|----------------------|------|------|------|------|
| 1. Stand-over height                        |       |      |                      |      |      |      |      |
| Inches                                      | 28.5  | 30.4 | 31.2                 | 31.9 | 32.6 | 33.4 | 33.8 |
| Centimeters                                 | 72.4  | 77.1 | 79.2                 | 81.1 | 82.9 | 84.8 | 85.8 |
| 2. Top tube                                 |       |      |                      |      |      |      |      |
| Inches                                      | 20.1  | 20.9 | 21.7                 | 21.7 | 22.4 | 22.4 | 23.0 |
| Centimeters                                 | 51.0  | 53.0 | 55.0                 | 55.0 | 57.0 | 57.0 | 58.5 |
| 3. Stem extension (standard type, 17° drop) |       |      |                      |      |      |      |      |
| Millimeters                                 | 80    | 100  | 100                  | 100  | 120  | 120  | 120  |
| 4. Reach (top tube + stem reach)            |       |      |                      |      |      |      |      |
| Inches                                      | 23.2  | 24.8 | 25.6                 | 25.6 | 27.2 | 27.2 | 27.8 |
| Centimeters                                 | 59    | 63   | 65                   | 65   | 69   | 69   | 70.5 |
| 5. Handlebar width (25.4 mm diameter)       |       |      |                      |      |      |      |      |
| Millimeters                                 | 390   | 410  | 410                  | 410  | 430  | 430  | 430  |
| 6. Crank arm length                         |       |      |                      |      |      |      |      |
| Millimeters                                 | 165   | 170  | 170                  | 170  | 175  | 175  | 175  |
| 7. Steerer length, threaded                 |       |      |                      |      |      |      |      |
| Inches                                      | 5.0   | 5.7  | 6.5                  | 7.3  | 8.0  | 8.8  | 9.2  |
| Millimeters                                 | 126   | 145  | 165                  | 185  | 204  | 224  | 233  |
| 8. Head tube length                         |       |      |                      |      |      |      |      |
| Inches                                      | 3.4   | 4.1  | 4.9                  | 5.7  | 6.5  | 7.2  | 7.6  |
| Millimeters                                 | 86    | 104  | 124                  | 145  | 165  | 183  | 193  |
| 9. Seatpost length (27.2 mm diameter)       |       |      |                      |      |      |      |      |
| Millimeters                                 | 250   | 250  | 250                  | 250  | 250  | 250  | 250  |
| 10. Gearing                                 | 42/53 |      | 13-15-17-19-21-23-26 |      |      |      |      |

### General Information

|                  |                                          |
|------------------|------------------------------------------|
| Hubset, Type     | HyperGlide                               |
| Spoke number     | 32                                       |
| Spokes, Front    | 299 14 ga.                               |
| Rear(D/ND)       | 296/298 14 ga.                           |
| Tire Size        | 700 x 25                                 |
| Front Derailleur | 34.9 mm/1 <sup>3</sup> / <sub>8</sub> in |
| Bottom bracket   | BB-UN51                                  |
| Shell Width      | 68                                       |
| Axle length      | 115                                      |
| R. dropout width | 128                                      |
| Headset size     | 22.2/30.2/26.4                           |
| Weight           | 22.6 lb/10.3 kg.                         |

### Upgrades

- Racing bike
- Look PM56 ARC pedal
- System 2 racing saddle
- Titan Tech rims and IsoTech 3 tires are light, yet durable
- Modified, wide ratio racing gearing

## Model 2100

| Sizes                                       | 47    | 52   | 54                   | 56   | 58   | 60   | 62   |
|---------------------------------------------|-------|------|----------------------|------|------|------|------|
| 1. Stand-over height                        |       |      |                      |      |      |      |      |
| Inches                                      | 28.5  | 30.4 | 31.2                 | 31.9 | 32.6 | 33.4 | 33.8 |
| Centimeters                                 | 72.4  | 77.1 | 79.2                 | 81.1 | 82.9 | 84.8 | 85.8 |
| 2. Top tube                                 |       |      |                      |      |      |      |      |
| Inches                                      | 20.1  | 20.9 | 21.7                 | 21.7 | 22.4 | 22.4 | 23.0 |
| Centimeters                                 | 51.0  | 53.0 | 55.0                 | 55.0 | 57.0 | 57.0 | 58.5 |
| 3. Stem extension (standard type, 17° drop) |       |      |                      |      |      |      |      |
| Millimeters                                 | 80    | 100  | 100                  | 100  | 120  | 120  | 120  |
| 4. Reach (top tube + stem reach)            |       |      |                      |      |      |      |      |
| Inches                                      | 23.2  | 24.8 | 25.6                 | 25.6 | 27.2 | 27.2 | 27.8 |
| Centimeters                                 | 59    | 63   | 65                   | 65   | 69   | 69   | 70.5 |
| 5. Handlebar width (25.4 mm diameter)       |       |      |                      |      |      |      |      |
| Millimeters                                 | 390   | 410  | 410                  | 410  | 430  | 430  | 430  |
| 6. Crank arm length                         |       |      |                      |      |      |      |      |
| Millimeters                                 | 165   | 170  | 170                  | 170  | 175  | 175  | 175  |
| 7. Steerer length, threaded                 |       |      |                      |      |      |      |      |
| Inches                                      | 4.7   | 5.5  | 6.2                  | 7.0  | 7.8  | 8.6  | 8.9  |
| Millimeters                                 | 119   | 138  | 158                  | 178  | 197  | 217  | 226  |
| 8. Head tube length                         |       |      |                      |      |      |      |      |
| Inches                                      | 3.4   | 4.1  | 4.9                  | 5.7  | 6.5  | 7.2  | 7.6  |
| Millimeters                                 | 86    | 104  | 124                  | 145  | 165  | 183  | 193  |
| 9. Seatpost length (27.2 mm diameter)       |       |      |                      |      |      |      |      |
| Millimeters                                 | 250   | 250  | 250                  | 250  | 250  | 250  | 250  |
| 10. Gearing                                 | 42/53 |      | 13-15-17-19-21-23-26 |      |      |      |      |

### General Information

|                  |                                          |
|------------------|------------------------------------------|
| Hubset, Type     | HyperGlide                               |
| Spoke number     | 32                                       |
| Spokes, Front    | 299 14 ga.                               |
| Rear(D/ND)       | 296/298 14 ga.                           |
| Tire Size        | 700 x 25                                 |
| Front Derailleur | 34.9 mm/1 <sup>3</sup> / <sub>8</sub> in |
| Bottom bracket   | BB-UN51                                  |
| Shell Width      | 68                                       |
| Axle length      | 115                                      |
| R. dropout width | 128                                      |
| Headset size     | 22.2/30.2/26.4                           |
| Weight           | 21.9 lb/10.0 kg.                         |

### Upgrades

- Carbon fiber composite tubing
- Trek epoxy bonded aluminum fork
- Modified racing gearing
- Shimano 105SC derailleurs and shifters



## Model 2200

| Sizes                                       | 47    | 50    | 52                      | 54   | 56    | 58    | 60   | 62   |
|---------------------------------------------|-------|-------|-------------------------|------|-------|-------|------|------|
| 1. Stand-over height                        |       |       |                         |      |       |       |      |      |
| Inches                                      | 28.5  | 29.6  | 30.4                    | 31.2 | 31.9  | 32.6  | 33.4 | 33.8 |
| Centimeters                                 | 72.4  | 75.3  | 77.1                    | 79.2 | 81.1  | 82.9  | 84.8 | 85.8 |
| 2. Top tube                                 |       |       |                         |      |       |       |      |      |
| Inches                                      | 20.1  | 20.9  | 20.9                    | 21.7 | 21.7  | 22.4  | 22.4 | 23.0 |
| Centimeters                                 | 51.0  | 53.0  | 53.0                    | 55.0 | 55.0  | 57.0  | 57.0 | 58.5 |
| 3. Stem extension (standard type, 17° drop) |       |       |                         |      |       |       |      |      |
| Millimeters                                 | 85    | 100   | 100                     | 100  | 115   | 115   | 130  | 130  |
| 4. Reach (top tube + stem reach)            |       |       |                         |      |       |       |      |      |
| Inches                                      | 23.4  | 24.8  | 24.8                    | 25.6 | 26.2  | 27.0  | 27.6 | 28.1 |
| Centimeters                                 | 59.5  | 63    | 63                      | 65   | 66.5  | 68.5  | 70   | 71.5 |
| 5. Handlebar width (26.0 mm diameter)       |       |       |                         |      |       |       |      |      |
| Centimeters                                 | 40    | 40    | 40                      | 42   | 42    | 42    | 44   | 44   |
| 6. Crank arm length                         |       |       |                         |      |       |       |      |      |
| Millimeters                                 | 167.5 | 167.5 | 170                     | 170  | 172.5 | 172.5 | 175  | 175  |
| 7. Steerer length, threaded                 |       |       |                         |      |       |       |      |      |
| Inches                                      | 4.7   | 4.7   | 5.5                     | 6.2  | 7.0   | 7.8   | 8.6  | 8.9  |
| Millimeters                                 | 119   | 119   | 138                     | 158  | 178   | 197   | 217  | 226  |
| 8. Head tube length                         |       |       |                         |      |       |       |      |      |
| Inches                                      | 3.4   | 3.4   | 4.1                     | 4.9  | 5.7   | 6.5   | 7.2  | 7.6  |
| Millimeters                                 | 86    | 86    | 104                     | 124  | 145   | 165   | 183  | 193  |
| 9. Seatpost length (27.2 mm diameter)       |       |       |                         |      |       |       |      |      |
| Millimeters                                 | 250   | 250   | 250                     | 250  | 250   | 250   | 250  | 250  |
| 10. Gearing                                 | 39/53 |       | 13-14-15-17-19-21-23-26 |      |       |       |      |      |

### General Information

|                  |                                          |
|------------------|------------------------------------------|
| Hubset, Type     | HyperGlide                               |
| Spoke number     | 32                                       |
| Spokes, Front    | 296 14/15 ga.                            |
| Rear(D/ND)       | 294/295 14/15ga.                         |
| Tire Size        | 700 x 25                                 |
| Front Derailleur | 34.9 mm/1 <sup>3</sup> / <sub>8</sub> in |
| Bottom bracket   | BB-UN71                                  |
| Shell Width      | 68                                       |
| Axle length      | 115                                      |
| R. dropout width | 128                                      |
| Headset size     | 22.2/30.2/26.4                           |
| Weight           | 21.7 lb/ 9.9 kg.                         |

### Upgrades

- STI Dual control brake/shift levers
- 8 speed cassette
- Matrix Sonic rims and Iso Tech 5 Lite tires
- System 2 handlebars, System 3 saddle and seatpost
- Shimano 105SC hubs and brakes (full group)

## Model 2300

| Sizes                                       | 47    | 50    | 52                      | 54   | 56    | 58    | 60   | 62   |
|---------------------------------------------|-------|-------|-------------------------|------|-------|-------|------|------|
| 1. Stand-over height                        |       |       |                         |      |       |       |      |      |
| Inches                                      | 28.5  | 29.6  | 30.4                    | 31.2 | 31.9  | 32.6  | 33.4 | 33.8 |
| Centimeters                                 | 72.4  | 75.3  | 77.1                    | 79.2 | 81.1  | 82.9  | 84.8 | 85.8 |
| 2. Top tube                                 |       |       |                         |      |       |       |      |      |
| Inches                                      | 20.1  | 20.9  | 20.9                    | 21.7 | 21.7  | 22.4  | 22.4 | 23.0 |
| Centimeters                                 | 51.0  | 53.0  | 53.0                    | 55.0 | 55.0  | 57.0  | 57.0 | 58.5 |
| 3. Stem extension (Direct Connect, 0° rise) |       |       |                         |      |       |       |      |      |
| Millimeters                                 | 100   | 100   | 110                     | 110  | 120   | 120   | 130  | 130  |
| 4. Reach (top tube + stem reach)            |       |       |                         |      |       |       |      |      |
| Inches                                      | 23.9  | 24.6  | 25.0                    | 25.8 | 26.2  | 27.0  | 27.3 | 27.9 |
| Centimeters                                 | 60.6  | 62.6  | 63.5                    | 65.5 | 66.5  | 68.5  | 69.4 | 70.9 |
| 5. Handlebar width (26.0 mm diameter)       |       |       |                         |      |       |       |      |      |
| Centimeters                                 | 40    | 40    | 40                      | 42   | 42    | 42    | 44   | 44   |
| 6. Crank arm length                         |       |       |                         |      |       |       |      |      |
| Millimeters                                 | 167.5 | 167.5 | 170                     | 170  | 172.5 | 172.5 | 175  | 175  |
| 7. Steerer length, non-thread               |       |       |                         |      |       |       |      |      |
| Inches                                      | 6.2   | 6.2   | 7.0                     | 7.8  | 8.5   | 9.3   | 10.0 | 10.4 |
| Millimeters                                 | 158   | 158   | 177                     | 197  | 217   | 236   | 256  | 265  |
| 8. Head tube length                         |       |       |                         |      |       |       |      |      |
| Inches                                      | 3.4   | 3.4   | 4.1                     | 4.9  | 5.7   | 6.5   | 7.2  | 7.6  |
| Millimeters                                 | 86    | 86    | 104                     | 124  | 145   | 165   | 183  | 193  |
| 9. Seatpost length (27.2 mm diameter)       |       |       |                         |      |       |       |      |      |
| Millimeters                                 | 250   | 250   | 250                     | 250  | 250   | 250   | 250  | 250  |
| 10. Gearing                                 | 39/53 |       | 12-13-14-15-17-19-21-23 |      |       |       |      |      |

### General Information

|                  |                                          |
|------------------|------------------------------------------|
| Hubset, Type     | HyperGlide                               |
| Spoke number     | 32                                       |
| Spokes, Front    | 296 14/15 ga.                            |
| Rear(D/ND)       | 294/295 14/15ga.                         |
| Tire Size        | 700 x 25                                 |
| Front Derailleur | 34.9 mm/1 <sup>3</sup> / <sub>8</sub> in |
| Bottom bracket   | BB-UN71                                  |
| Shell Width      | 68                                       |
| Axle length      | 115                                      |
| R. dropout width | 128                                      |
| Headset size     | 22.2/30.2/26.4                           |
| Weight           | 21.3 lb/ 9.7 kg.                         |

### Upgrades

- Shimano Ultegra group w/STI
- AheadSet system
- 14/15 double butted spokes
- 39/53, 12-23 8 spd -full race gearing
- Look PM196 ARC pedals



## Model 5200

| Sizes                                       | 50    | 52   | 54                      | 56    | 58    | 60   | 62   |
|---------------------------------------------|-------|------|-------------------------|-------|-------|------|------|
| 1. Stand-over height                        |       |      |                         |       |       |      |      |
| Inches                                      | 29.5  | 29.9 | 30.4                    | 31.2  | 31.9  | 32.7 | 33.4 |
| Centimeters                                 | 74.9  | 75.9 | 77.3                    | 79.3  | 81.1  | 83.0 | 84.8 |
| 2. Top tube                                 |       |      |                         |       |       |      |      |
| Inches                                      | 20.4  | 20.8 | 21.5                    | 22.0  | 22.4  | 22.8 | 23.2 |
| Centimeters                                 | 51.8  | 52.8 | 54.5                    | 56.0  | 57.0  | 58.0 | 59.0 |
| 3. Stem extension (Direct Connect, 0° rise) |       |      |                         |       |       |      |      |
| Millimeters                                 | 100   | 110  | 110                     | 120   | 120   | 130  | 130  |
| 4. Reach (top tube + stem reach)            |       |      |                         |       |       |      |      |
| Inches                                      | 24.2  | 24.9 | 25.6                    | 26.6  | 27.0  | 27.7 | 28.1 |
| Centimeters                                 | 61.4  | 63.3 | 65.0                    | 67.5  | 68.5  | 70.4 | 71.4 |
| 5. Handlebar width (26.0 mm diameter)       |       |      |                         |       |       |      |      |
| Centimeters                                 | 40    | 40   | 42                      | 42    | 42    | 44   | 44   |
| 6. Crank arm length                         |       |      |                         |       |       |      |      |
| Millimeters                                 | 167.5 | 170  | 170                     | 172.5 | 172.5 | 175  | 175  |
| 7. Steerer length, non-threaded             |       |      |                         |       |       |      |      |
| Inches                                      | 6.8   | 6.8  | 7.1                     | 7.8   | 8.5   | 9.3  | 9.9  |
| Millimeters                                 | 173   | 173  | 180                     | 197   | 216   | 235  | 253  |
| 8. Head tube length                         |       |      |                         |       |       |      |      |
| Inches                                      | 3.8   | 3.8  | 4.1                     | 4.8   | 5.5   | 6.2  | 7.0  |
| Millimeters                                 | 97    | 97   | 104                     | 121   | 140   | 158  | 177  |
| 9. Seatpost length (27.2 mm diameter)       |       |      |                         |       |       |      |      |
| Millimeters                                 | 250   | 250  | 250                     | 250   | 250   | 250  | 250  |
| 10. Gearing                                 | 39/53 |      | 12-13-14-15-17-19-21-23 |       |       |      |      |

## General Information

|                  |                  |
|------------------|------------------|
| Hubset, Type     | HyperGlide       |
| Spoke number     | 32               |
| Spokes, Front    | 296 14/15 ga.    |
| Rear(D/ND)       | 294/295 14/15ga. |
| Tire Size        | 700x25           |
| Front Derailleur | brazed-on type   |
| Bottom bracket   | BB-UN71          |
| Shell Width      | 68               |
| Axle length      | 115              |
| R. dropout width | 128              |
| Headset size     | 22.2/30.2/26.4   |
| Weight           | 19.9 lb/9.0 kg.  |

## Upgrades

- OCLV carbon fiber composite frame
- OCLV carbon fiber composite fork
- Lightest production frameset in the world
- "Custom" sizing of both tube lengths and stiffness of frame

## Model 5500

| Sizes                                       | 50    | 52   | 54                      | 56    | 58    | 60   | 62   |
|---------------------------------------------|-------|------|-------------------------|-------|-------|------|------|
| 1. Stand-over height                        |       |      |                         |       |       |      |      |
| Inches                                      | 29.5  | 29.9 | 30.4                    | 31.2  | 31.9  | 32.7 | 33.4 |
| Centimeters                                 | 74.9  | 75.9 | 77.3                    | 79.3  | 81.1  | 83.0 | 84.8 |
| 2. Top tube                                 |       |      |                         |       |       |      |      |
| Inches                                      | 20.4  | 20.8 | 21.5                    | 22.0  | 22.4  | 22.8 | 23.2 |
| Centimeters                                 | 51.8  | 52.8 | 54.5                    | 56.0  | 57.0  | 58.0 | 59.0 |
| 3. Stem extension (Direct Connect, 0° rise) |       |      |                         |       |       |      |      |
| Millimeters                                 | 100   | 110  | 110                     | 120   | 120   | 130  | 130  |
| 4. Reach (top tube + stem reach)            |       |      |                         |       |       |      |      |
| Inches                                      | 24.2  | 24.9 | 25.6                    | 26.6  | 27.0  | 27.7 | 28.1 |
| Centimeters                                 | 61.4  | 63.3 | 65.0                    | 67.5  | 68.5  | 70.4 | 71.4 |
| 5. Handlebar width (26.0 mm diameter)       |       |      |                         |       |       |      |      |
| Centimeters                                 | 40    | 40   | 42                      | 42    | 42    | 44   | 44   |
| 6. Crank arm length                         |       |      |                         |       |       |      |      |
| Millimeters                                 | 167.5 | 170  | 172.5                   | 172.5 | 172.5 | 175  | 175  |
| 7. Steerer length, non-threaded             |       |      |                         |       |       |      |      |
| Inches                                      | 7.1   | 7.1  | 7.4                     | 8.1   | 8.8   | 9.5  | 10.3 |
| Millimeters                                 | 180   | 180  | 187                     | 204   | 223   | 242  | 260  |
| 8. Head tube length                         |       |      |                         |       |       |      |      |
| Inches                                      | 3.8   | 3.8  | 4.1                     | 4.8   | 5.5   | 6.2  | 7.0  |
| Millimeters                                 | 97    | 97   | 104                     | 121   | 140   | 158  | 177  |
| 9. Seatpost length (27.2 mm diameter)       |       |      |                         |       |       |      |      |
| Millimeters                                 | 235   | 235  | 235                     | 235   | 235   | 235  | 235  |
| 10. Gearing                                 | 39/53 |      | 12-13-14-15-17-19-21-23 |       |       |      |      |

## General Information

|                  |                  |
|------------------|------------------|
| Hubset, Type     | HyperGlide       |
| Spoke number     | 32               |
| Spokes, Front    | 297 14/15 ga.    |
| Rear(D/ND)       | 294/296 14/15ga. |
| Tire Size        | 700 x 23         |
| Front Derailleur | brazed-on type   |
| Bottom bracket   | BB-UN91          |
| Shell Width      | 68               |
| Axle length      | 115              |
| R. dropout width | 128              |
| Headset size     | 22.2/30.2/26.4   |
| Weight           | 19.7 lb/ 9.0 kg. |

## Upgrades

- Shimano Dura-Ace STI group
- Chris King precision headset
- System 2 handlebars, System 4 alloy direct connect stem
- Vetta VSL titanium saddle on American Classic seatpost
- Iso Tech 6 Lite tires



## Model 5900

| Sizes                                       | 50    | 52                      | 54   | 56    | 58    | 60   | 62   |
|---------------------------------------------|-------|-------------------------|------|-------|-------|------|------|
| 1. Stand-over height                        |       |                         |      |       |       |      |      |
| Inches                                      | 29.5  | 29.9                    | 30.4 | 31.2  | 31.9  | 32.7 | 33.4 |
| Centimeters                                 | 74.9  | 75.9                    | 77.3 | 79.3  | 81.1  | 83.0 | 84.8 |
| 2. Top tube                                 |       |                         |      |       |       |      |      |
| Inches                                      | 20.4  | 20.8                    | 21.5 | 22.0  | 22.4  | 22.8 | 23.2 |
| Centimeters                                 | 51.8  | 52.8                    | 54.5 | 56.0  | 57.0  | 58.0 | 59.0 |
| 3. Stem extension (Direct Connect, 0° rise) |       |                         |      |       |       |      |      |
| Millimeters                                 | 90    | 90                      | 110  | 110   | 110   | 130  | 130  |
| 4. Reach (top tube + stem reach)            |       |                         |      |       |       |      |      |
| Inches                                      | 23.8  | 24.2                    | 25.6 | 26.2  | 26.6  | 27.7 | 28.1 |
| Centimeters                                 | 60.4  | 61.4                    | 65.0 | 66.5  | 67.5  | 70.4 | 71.4 |
| 5. Handlebar width (26.0 mm diameter)       |       |                         |      |       |       |      |      |
| Centimeters                                 | 40    | 40                      | 42   | 42    | 42    | 44   | 44   |
| 6. Crank arm length                         |       |                         |      |       |       |      |      |
| Millimeters                                 | 167.5 | 170                     | 170  | 172.5 | 172.5 | 175  | 175  |
| 7. Steerer length, non-threaded             |       |                         |      |       |       |      |      |
| Inches                                      | 6.5   | 6.5                     | 6.8  | 7.5   | 8.2   | 9.0  | 9.7  |
| Millimeters                                 | 166   | 166                     | 173  | 190   | 209   | 228  | 246  |
| 8. Head tube length                         |       |                         |      |       |       |      |      |
| Inches                                      | 3.8   | 3.8                     | 4.1  | 4.8   | 5.5   | 6.2  | 7.0  |
| Millimeters                                 | 97    | 97                      | 104  | 121   | 140   | 158  | 177  |
| 9. Seatpost length (27.2 mm diameter)       |       |                         |      |       |       |      |      |
| Millimeters                                 | 235   | 235                     | 235  | 235   | 235   | 235  | 235  |
| 10. Gearing                                 | 39/53 | 12-13-14-15-17-19-21-23 |      |       |       |      |      |

## General Information

|                  |                  |
|------------------|------------------|
| Hubset, Type     | HyperGlide       |
| Spoke number     | 28F / 32R        |
| Spokes, Front    | 304 14/15 ga.    |
| Rear(D/ND)       | 299/301 14/15ga. |
| Tire Size        | Tubular          |
| Front Derailleur | Braze-on type    |
| Bottom bracket   | White Ind. Ti    |
| Shell Width      | 68               |
| Axle length      | 117              |
| R. dropout width | 128              |
| Headset size     | 22.2/30.2/26.4   |
| Weight           | 17.0 lb/ 7.5 kg. |

## Upgrades

- Matrix Photon rims with Continental 240 Competition tubular tires
- Hugi hubset (28°F, 32°R)
- Titanium parts- Ibis stem, American Classic seatpost, White bottom bracket, Salsa quick releases, Selle Italia Flite Evolution saddle, titanium cassette cogs



# Multi Track/Metro Track

## Model 700

| Sizes                                          | 15       | 17   | 19   | 21                | 23   | 17W  | 20W  |
|------------------------------------------------|----------|------|------|-------------------|------|------|------|
| 1. Stand-over height                           |          |      |      |                   |      |      |      |
| Inches                                         | 28.3     | 29.4 | 30.6 | 31.9              | 33.7 | NA   | NA   |
| Centimeters                                    | 71.9     | 74.6 | 77.7 | 81.1              | 85.6 |      |      |
| 2. Top tube                                    |          |      |      |                   |      |      |      |
| Inches                                         | 20.9     | 21.3 | 21.9 | 22.2              | 22.6 | 21.0 | 21.1 |
| Centimeters                                    | 53.0     | 54.0 | 55.5 | 56.5              | 57.5 | 53.3 | 53.6 |
| 3. Stem extension (standard type, 45° rise)    |          |      |      |                   |      |      |      |
| Millimeters                                    | 100      | 100  | 100  | 100               | 100  | 100  | 100  |
| 4. Reach (top tube + stem reach)               |          |      |      |                   |      |      |      |
| Inches                                         | 22.7     | 23.1 | 23.7 | 24.1              | 24.5 | 22.8 | 23.0 |
| Centimeters                                    | 57.7     | 58.7 | 60.2 | 61.2              | 62.2 | 58.0 | 58.3 |
| 5. Handlebar width (25.4 mm diameter, 6° bend) |          |      |      |                   |      |      |      |
| Millimeters                                    | 610      | 610  | 610  | 610               | 610  | 610  | 610  |
| 6. Crank arm length                            |          |      |      |                   |      |      |      |
| Millimeters                                    | 170      | 170  | 170  | 170               | 170  | 170  | 170  |
| 7. Steerer length, threaded                    |          |      |      |                   |      |      |      |
| Inches                                         | 4.9      | 4.9  | 5.3  | 6.1               | 8.1  | 6.5  | 7.7  |
| Millimeters                                    | 125      | 125  | 135  | 155               | 205  | 165  | 195  |
| 8. Head tube length                            |          |      |      |                   |      |      |      |
| Inches                                         | 3.3      | 3.3  | 3.7  | 4.5               | 6.5  | 4.9  | 6.1  |
| Millimeters                                    | 85       | 85   | 95   | 115               | 165  | 125  | 155  |
| 9. Seatpost length (26.8 mm diameter)          |          |      |      |                   |      |      |      |
| Millimeters                                    | 300      | 300  | 300  | 300               | 300  | 300  | 300  |
| 10. Gearing                                    | 28/38/48 |      |      | 14-16-18-21-24-28 |      |      |      |

### General Information

|                  |                   |
|------------------|-------------------|
| Hubset, Type     | HyperGlide        |
| Spoke number     | 36                |
| Spokes, Front    | 296 14 ga.        |
| Rear(D/ND)       | 293/295 14 ga.    |
| Tire Size        | 700 x 35          |
| Front Derailleur | 28.6 mm/1 1/8"    |
| Bottom bracket   | BB-CS11           |
| Shell Width      | 68                |
| Axle length      | 118               |
| R. dropout width | 135               |
| Headset size     | 22.2/30.2/26.4    |
| Weight           | 27.9 lb/ 12.7 kg. |

### Upgrades

- GripShift with wide range 18 speed gearing
- Shimano M System brakes for good stopping
- Hi-rise bar and stem combos for upright positioning
- Micro adjust seat post
- Cartridge bottom bracket
- Front and rear wheel quick releases



## Model 720

| Sizes                                       | 15       | 17   | 19   | 21                   | 23   | 17W  | 20W  |
|---------------------------------------------|----------|------|------|----------------------|------|------|------|
| 1. Stand-over height                        |          |      |      |                      |      |      |      |
| Inches                                      | 28.3     | 29.4 | 30.6 | 31.9                 | 33.7 | NA   | NA   |
| Centimeters                                 | 71.9     | 74.6 | 77.7 | 81.1                 | 85.6 |      |      |
| 2. Top tube                                 |          |      |      |                      |      |      |      |
| Inches                                      | 20.9     | 21.3 | 21.9 | 22.2                 | 22.6 | 21.0 | 21.1 |
| Centimeters                                 | 53.0     | 54.0 | 55.5 | 56.5                 | 57.5 | 53.3 | 53.6 |
| 3. Stem extension (standard type, 45° rise) |          |      |      |                      |      |      |      |
| Millimeters                                 | 100      | 100  | 100  | 100                  | 100  | 100  | 100  |
| 4. Reach (top tube + stem reach)            |          |      |      |                      |      |      |      |
| Inches                                      | 22.7     | 23.1 | 23.7 | 24.1                 | 24.5 | 22.8 | 23.0 |
| Centimeters                                 | 57.7     | 58.7 | 60.2 | 61.2                 | 62.2 | 58.0 | 58.3 |
| 5. Handlebar width (25.4 mm diameter)       |          |      |      |                      |      |      |      |
| Millimeters                                 | 610      | 610  | 610  | 610                  | 610  | 610  | 610  |
| 6. Crank arm length                         |          |      |      |                      |      |      |      |
| Millimeters                                 | 170      | 170  | 170  | 175                  | 175  | 170  | 170  |
| 7. Steerer length, threaded                 |          |      |      |                      |      |      |      |
| Inches                                      | 4.9      | 4.9  | 5.3  | 6.1                  | 8.1  | 6.5  | 7.7  |
| Millimeters                                 | 125      | 125  | 135  | 155                  | 205  | 165  | 195  |
| 8. Head tube length                         |          |      |      |                      |      |      |      |
| Inches                                      | 3.3      | 3.3  | 3.7  | 4.5                  | 6.5  | 4.9  | 6.1  |
| Millimeters                                 | 85       | 85   | 95   | 115                  | 165  | 125  | 155  |
| 9. Seatpost length (26.8 mm diameter)       |          |      |      |                      |      |      |      |
| Millimeters                                 | 300      | 300  | 300  | 300                  | 300  | 300  | 300  |
| 10. Gearing                                 | 28/38/48 |      |      | 12-14-16-18-21-24-28 |      |      |      |

### General Information

|                  |                                         |
|------------------|-----------------------------------------|
| Hubset, Type     | HyperGlide                              |
| Spoke number     | 36                                      |
| Spokes, Front    | 296 14 ga.                              |
| Rear(D/ND)       | 293/295 14 ga.                          |
| Tire Size        | 700 x 35                                |
| Front Derailleur | 28.6 mm/1 <sup>1</sup> / <sub>8</sub> " |
| Bottom bracket   | BB-LP20                                 |
| Shell Width      | 68                                      |
| Axle length      | 118                                     |
| R. dropout width | 135                                     |
| Headset size     | 22.2/30.2/26.4                          |
| Weight           | 27.8 lb/12.6 kg.                        |

### Upgrades

- Full Cro-Moly steel frame and fork
- 21 speed wide ratio gearing with higher top gear
- Cassette style rear wheel for added durability
- System 1 Gel Lite saddle
- Shimano Altus A-20 crank, brakes, and derailleurs

## Model 750

| Sizes                                   | 17       | 19     | 21                   | 23     |
|-----------------------------------------|----------|--------|----------------------|--------|
| 1. Stand-over height                    |          |        |                      |        |
| Inches                                  | 28.6     | 30.6   | 31.8                 | 33.7   |
| Centimeters                             | 72.7     | 76.6   | 80.8                 | 85.6   |
| 2. Top tube                             |          |        |                      |        |
| Inches                                  | 21.3     | 21.9   | 22.2                 | 22.6   |
| Centimeters                             | 54.0     | 55.5   | 56.5                 | 57.5   |
| 3. Stem extension (standard type/ rise) |          |        |                      |        |
| Millimeters                             | 105/25   | 120/25 | 120/25               | 135/15 |
| 4. Reach (top tube + stem reach)        |          |        |                      |        |
| Inches                                  | 24.5     | 25.6   | 26.0                 | 27.2   |
| Centimeters                             | 62.3     | 65.0   | 66.0                 | 69.2   |
| 5. Handlebar width (25.4 mm diameter)   |          |        |                      |        |
| Millimeters                             | 560      | 560    | 560                  | 560    |
| 6. Crank arm length                     |          |        |                      |        |
| Millimeters                             | 170      | 175    | 175                  | 175    |
| 7. Steerer length, threaded             |          |        |                      |        |
| Inches                                  | 5.4      | 5.4    | 6.3                  | 8.3    |
| Millimeters                             | 136      | 136    | 159                  | 210    |
| 8. Head tube length                     |          |        |                      |        |
| Inches                                  | 3.7      | 3.7    | 4.6                  | 6.6    |
| Millimeters                             | 93       | 93     | 116                  | 167    |
| 9. Seatpost length (26.8 mm diameter)   |          |        |                      |        |
| Millimeters                             | 300      | 300    | 300                  | 300    |
| 10. Gearing                             | 30/40/50 |        | 12-14-16-18-21-24-28 |        |

### General Information

|                  |                                         |
|------------------|-----------------------------------------|
| Hubset, Type     | HyperGlide                              |
| Spoke number     | 32                                      |
| Spokes, Front    | 299 14 ga.                              |
| Rear(D/ND)       | 297/298 14 ga.                          |
| Tire Size        | 700 x 38                                |
| Front Derailleur | 28.6 mm/1 <sup>1</sup> / <sub>8</sub> " |
| Bottom bracket   | BB-UN51                                 |
| Shell Width      | 68                                      |
| Axle length      | 113                                     |
| R. dropout width | 135                                     |
| Headset size     | 22.2/30.2/26.4                          |
| Weight           | 26.1 lb/11.9 kg.                        |

### Upgrades

- U.S. built low temperature brazed True Temper double butted Cro-Moly
- Matrix Titan Tour rims with Trek Invert II 700x38 tires
- System 1 stem, alloy handlebars, and pedals with toe clips
- Stainless steel spokes
- System 2 Gel Lite saddle



## Model 7600

| Sizes                                           | 16.5     | 18    | 20                   | 22     |
|-------------------------------------------------|----------|-------|----------------------|--------|
| 1. Stand-over height                            |          |       |                      |        |
| Inches                                          | 29.2     | 30.1  | 31.3                 | 32.9   |
| Centimeters                                     | 74.3     | 76.4  | 79.4                 | 83.6   |
| 2. Top tube                                     |          |       |                      |        |
| Inches                                          | 21.7     | 21.9  | 22.6                 | 23.0   |
| Centimeters                                     | 55.0     | 56.6  | 57.4                 | 58.5   |
| 3. Stem extension (standard type, degrees rise) |          |       |                      |        |
| Millimeters                                     | 120/5    | 120/5 | 135/10               | 150/10 |
| 4. Reach (top tube + stem reach)                |          |       |                      |        |
| Inches                                          | 25.5     | 26.1  | 27.0                 | 28.0   |
| Centimeters                                     | 64.8     | 66.3  | 68.7                 | 71.1   |
| 5. Handlebar width (25.4 mm diameter, 5° bend)  |          |       |                      |        |
| Millimeters                                     | 560      | 560   | 560                  | 560    |
| 6. Crank arm length                             |          |       |                      |        |
| Millimeters                                     | 175      | 175   | 175                  | 175    |
| 7. Steerer length, OS, threaded                 |          |       |                      |        |
| Inches                                          | 5.2      | 5.2   | 6.1                  | 8.2    |
| Millimeters                                     | 131      | 131   | 154                  | 207    |
| 8. Head tube length                             |          |       |                      |        |
| Inches                                          | 3.7      | 3.7   | 4.6                  | 6.6    |
| Millimeters                                     | 93       | 93    | 116                  | 167    |
| 9. Seatpost length (27.2 mm diameter)           |          |       |                      |        |
| Millimeters                                     | 300      | 300   | 300                  | 300    |
| 10. Gearing                                     | 20/32/42 |       | 11-12-13-14-15-17-19 |        |

### General Information

|                  |                                         |
|------------------|-----------------------------------------|
| Hubset, Type     | HyperGlide                              |
| Spoke number     | 32                                      |
| Spokes, Front    | 300 14 ga.                              |
| Rear(D/ND)       | 298/299 14 ga.                          |
| Tire Size        | 700x38                                  |
| Front Derailleur | 34.9 mm/1 <sup>3</sup> / <sub>8</sub> " |
| Bottom bracket   | BB-UN51                                 |
| Shell Width      | 68                                      |
| Axle length      | 118                                     |
| R. dropout width | 135                                     |
| Headset size     | 25.4/34.0/30.0                          |
| Weight           | 24.5 lb/11.1 kg.                        |

### Upgrades

- Bonded Easton Program aluminum frame
- Shimano CX400 hybrid group
- System 2 alloy handlebars (170 gm), System 2 pedals
- Matrix Journey rims
- OS stem, headset, and fork

## Model 7900

| Sizes                                           | 16.5     | 18    | 20                   | 22     |
|-------------------------------------------------|----------|-------|----------------------|--------|
| 1. Stand-over height                            |          |       |                      |        |
| Inches                                          | 29.2     | 30.1  | 31.3                 | 32.9   |
| Centimeters                                     | 74.3     | 76.4  | 79.4                 | 83.6   |
| 2. Top tube                                     |          |       |                      |        |
| Inches                                          | 21.7     | 21.9  | 22.6                 | 23.0   |
| Centimeters                                     | 54.0     | 55.5  | 56.5                 | 57.5   |
| 3. Stem extension (standard type, degrees rise) |          |       |                      |        |
| Millimeters                                     | 120/5    | 120/5 | 135/10               | 150/10 |
| 4. Reach (top tube + stem reach)                |          |       |                      |        |
| Inches                                          | 25.5     | 26.1  | 27.0                 | 28.0   |
| Centimeters                                     | 64.8     | 66.3  | 68.7                 | 71.1   |
| 5. Handlebar width (25.4 mm diameter, 5° bend)  |          |       |                      |        |
| Millimeters                                     | 560      | 560   | 560                  | 560    |
| 6. Crank arm length                             |          |       |                      |        |
| Millimeters                                     | 175      | 175   | 175                  | 175    |
| 7. Steerer length, OS, threaded                 |          |       |                      |        |
| Inches                                          | 5.2      | 5.2   | 6.1                  | 8.2    |
| Millimeters                                     | 132      | 132   | 155                  | 208    |
| 8. Head tube length                             |          |       |                      |        |
| Inches                                          | 3.7      | 3.7   | 4.6                  | 6.6    |
| Millimeters                                     | 93       | 93    | 116                  | 167    |
| 9. Seatpost length (27.2 mm diameter)           |          |       |                      |        |
| Millimeters                                     | 300      | 300   | 300                  | 300    |
| 10. Gearing                                     | 20/32/42 |       | 11-12-13-14-15-17-19 |        |

### General Information

|                  |                                         |
|------------------|-----------------------------------------|
| Hubset, Type     | HyperGlide                              |
| Spoke number     | 32                                      |
| Spokes, Front    | 300 14/15 ga.                           |
| Rear(D/ND)       | 298/299 14/15 ga.                       |
| Tire Size        | 700x40                                  |
| Front Derailleur | 34.9 mm/1 <sup>3</sup> / <sub>8</sub> " |
| Bottom bracket   | BB-UN51                                 |
| Shell Width      | 68                                      |
| Axle length      | 118                                     |
| R. dropout width | 135                                     |
| Headset size     | 25.4/34.0/30.0                          |
| Weight           | 24.3 lb/11.0 kg.                        |

### Upgrades

- Carbon fiber composite frame
- Shimano CX700 hybrid group
- System 3 alloy handlebars (150 gm) with System 1 barends
- DT 14/15 butted spokes
- System 3 pedals
- Trek Crewcut 700x40 tires



## Model 700M

| Sizes                                       | 15       | 17   | 19   | 21                | 23   | 17W  | 20W  |
|---------------------------------------------|----------|------|------|-------------------|------|------|------|
| 1. Stand-over height                        |          |      |      |                   |      |      |      |
| Inches                                      | 28.3     | 29.4 | 30.6 | 31.9              | 33.7 | NA   | NA   |
| Centimeters                                 | 71.9     | 74.6 | 77.7 | 81.1              | 85.6 |      |      |
| 2. Top tube                                 |          |      |      |                   |      |      |      |
| Inches                                      | 20.9     | 21.3 | 21.9 | 22.2              | 22.6 | 21.0 | 21.1 |
| Centimeters                                 | 53.0     | 54.0 | 55.5 | 56.5              | 57.5 | 53.3 | 53.6 |
| 3. Stem extension (standard type, 45° rise) |          |      |      |                   |      |      |      |
| Millimeters                                 | 100      | 100  | 100  | 100               | 100  | 100  | 100  |
| 4. Reach (top tube + stem reach)            |          |      |      |                   |      |      |      |
| Inches                                      | 22.7     | 23.1 | 23.7 | 24.1              | 24.5 | 22.8 | 23.0 |
| Centimeters                                 | 57.7     | 58.7 | 60.2 | 61.2              | 62.2 | 58.0 | 58.3 |
| 5. Handlebar width (25.4 mm diameter)       |          |      |      |                   |      |      |      |
| Millimeters                                 | 610      | 610  | 610  | 610               | 610  | 610  | 710  |
| 6. Crank arm length                         |          |      |      |                   |      |      |      |
| Millimeters                                 | 170      | 170  | 170  | 170               | 170  | 170  | 170  |
| 7. Steerer length, threaded                 |          |      |      |                   |      |      |      |
| Inches                                      | 4.9      | 4.9  | 5.3  | 6.1               | 8.1  | 6.5  | 7.7  |
| Millimeters                                 | 125      | 125  | 135  | 155               | 205  | 165  | 195  |
| 8. Head tube length                         |          |      |      |                   |      |      |      |
| Inches                                      | 3.3      | 3.3  | 3.7  | 4.5               | 6.5  | 4.9  | 6.1  |
| Millimeters                                 | 85       | 85   | 95   | 115               | 165  | 125  | 155  |
| 9. Seatpost length (26.8 mm diameter)       |          |      |      |                   |      |      |      |
| Millimeters                                 | 300      | 300  | 300  | 300               | 300  | 300  | 300  |
| 10. Gearing                                 | 30/40/50 |      |      | 14-16-18-21-24-28 |      |      |      |

### General Information

|                  |                            |
|------------------|----------------------------|
| Hubset, Type     | HyperGlide                 |
| Spoke number     | 36                         |
| Spokes, Front    | 296 14 ga.                 |
| Rear(D/ND)       | 293/295 14 ga.             |
| Tire Size        | 700x35                     |
| Front Derailleur | 28.6 mm/1 <sup>1/8</sup> " |
| Bottom bracket   | BB-CS11                    |
| Shell Width      | 68                         |
| Axle length      | 118                        |
| R. dropout width | 135                        |
| Headset size     | 22.2/30.2/26.4             |
| Weight           | 31.7 lb/14.4 kg            |

### Upgrades

- Similarly equipped to Model 700
- Trek MultiTrack 700x35 tires with reflective sidewalls
- Full fenders, Cibie halogen lights, Sanyo generator, rear rack, bell, kickstand
- Internal wiring for generator
- Flat handlebar on men's bike

## Model 750M

| Sizes                                   | 17       | 19     | 21                   | 23     |
|-----------------------------------------|----------|--------|----------------------|--------|
| 1. Stand-over height                    |          |        |                      |        |
| Inches                                  | 28.6     | 30.6   | 31.8                 | 33.7   |
| Centimeters                             | 72.7     | 76.6   | 80.8                 | 85.6   |
| 2. Top tube                             |          |        |                      |        |
| Inches                                  | 21.3     | 21.9   | 22.2                 | 22.6   |
| Centimeters                             | 54.0     | 55.5   | 56.5                 | 57.5   |
| 3. Stem extension (standard type/ rise) |          |        |                      |        |
| Millimeters                             | 105/25   | 120/25 | 120/25               | 135/15 |
| 4. Reach (top tube + stem reach)        |          |        |                      |        |
| Inches                                  | 24.5     | 25.6   | 26.0                 | 27.2   |
| Centimeters                             | 62.3     | 65.0   | 66.0                 | 69.2   |
| 5. Handlebar width (25.4 mm diameter)   |          |        |                      |        |
| Millimeters                             | 560      | 560    | 560                  | 560    |
| 6. Crank arm length                     |          |        |                      |        |
| Millimeters                             | 170      | 175    | 175                  | 175    |
| 7. Steerer length, threaded             |          |        |                      |        |
| Inches                                  | 5.4      | 5.4    | 6.3                  | 8.3    |
| Millimeters                             | 136      | 136    | 159                  | 210    |
| 8. Head tube length                     |          |        |                      |        |
| Inches                                  | 3.7      | 3.7    | 4.6                  | 6.6    |
| Millimeters                             | 93       | 93     | 116                  | 167    |
| 9. Seatpost length (26.8 mm diameter)   |          |        |                      |        |
| Millimeters                             | 300      | 300    | 300                  | 300    |
| 10. Gearing                             | 30/40/50 |        | 12-14-16-18-21-24-28 |        |

### General Information

|                  |                            |
|------------------|----------------------------|
| Hubset, Type     | HyperGlide                 |
| Spoke number     | 32                         |
| Spokes, Front    | 299 14 ga.                 |
| Rear(D/ND)       | 297/298 14 ga.             |
| Tire Size        | 700x35                     |
| Front Derailleur | 28.6 mm/1 <sup>1/8</sup> " |
| Bottom bracket   | BB-UN51                    |
| Shell Width      | 68                         |
| Axle length      | 113                        |
| R. dropout width | 135                        |
| Headset size     | 22.2/30.2/26.4             |
| Weight           | 29.5 lb/13.4 kg.           |

### Upgrades

- Similarly equipped to Model 750
- Invert K 700x35 tires with Kevlar belts
- Esge fenders, Union generator with taillight and Halogen headlamp, Trek Backrack, Trek Chime bell
- Internal wiring for generator



## Model 7600M

| Sizes                                           | 16.5     | 18    | 20                   | 22     |
|-------------------------------------------------|----------|-------|----------------------|--------|
| 1. Stand-over height                            |          |       |                      |        |
| Inches                                          | 29.2     | 30.1  | 31.3                 | 32.9   |
| Centimeters                                     | 74.3     | 76.4  | 79.4                 | 83.6   |
| 2. Top tube                                     |          |       |                      |        |
| Inches                                          | 21.7     | 21.9  | 22.6                 | 23.0   |
| Centimeters                                     | 54.0     | 55.5  | 56.5                 | 57.5   |
| 3. Stem extension (standard type, degrees rise) |          |       |                      |        |
| Millimeters                                     | 120/5    | 120/5 | 135/10               | 150/10 |
| 4. Reach (top tube + stem reach)                |          |       |                      |        |
| Inches                                          | 25.5     | 26.1  | 27.0                 | 28.0   |
| Centimeters                                     | 64.8     | 66.3  | 68.7                 | 71.1   |
| 5. Handlebar width (25.4 mm diameter, 5° bend)  |          |       |                      |        |
| Millimeters                                     | 560      | 560   | 560                  | 560    |
| 6. Crank arm length                             |          |       |                      |        |
| Millimeters                                     | 175      | 175   | 175                  | 175    |
| 7. Steerer length, OS, threaded                 |          |       |                      |        |
| Inches                                          | 5.2      | 5.2   | 6.1                  | 8.2    |
| Millimeters                                     | 131      | 131   | 154                  | 207    |
| 8. Head tube length                             |          |       |                      |        |
| Inches                                          | 3.7      | 3.7   | 4.6                  | 6.6    |
| Millimeters                                     | 93       | 93    | 116                  | 167    |
| 9. Seatpost length (27.2 mm diameter)           |          |       |                      |        |
| Millimeters                                     | 300      | 300   | 300                  | 300    |
| 10. Gearing                                     | 20/32/42 |       | 11-12-13-14-15-17-19 |        |

### General Information

|                  |                                        |
|------------------|----------------------------------------|
| Hubset, Type     | HyperGlide                             |
| Spoke number     | 32                                     |
| Spokes, Front    | 300 14 ga.                             |
| Rear(D/ND)       | 298/299 14 ga.                         |
| Tire Size        | 700x35                                 |
| Front Derailleur | 34.9mm/1 <sup>3</sup> / <sub>8</sub> " |
| Bottom bracket   | BB-UN51                                |
| Shell Width      | 68                                     |
| Axle length      | 118                                    |
| R. dropout width | 135                                    |
| Headset size     | 25.4/34.0/30.0                         |
| Weight           | 27.8 lb/12.6 kg.                       |

### Upgrades

- Similarly equipped to Model 7600
- Trek Invert K 700x35 tires with Kevlar belts
- Esge fenders, Union generator with taillight and Halogen headlamp, Trek Backrack, Trek Chime bell
- internal wiring for generator



# Mountain

## Model 800

| Sizes                                          | 14.5     | 16   | 18                | 20   | 22   | 14/24 17W | 20W  |
|------------------------------------------------|----------|------|-------------------|------|------|-----------|------|
| 1. Stand-over height                           |          |      |                   |      |      |           |      |
| Inches                                         | 27.5     | 28.4 | 29.3              | 30.8 | 32.7 | 26.6      | NA   |
| Centimeters                                    | 69.8     | 72.0 | 74.3              | 78.2 | 83.0 | 67.5      | NA   |
| 2. Top tube                                    |          |      |                   |      |      |           |      |
| Inches                                         | 20.3     | 21.1 | 22.1              | 22.4 | 22.8 | 19.4      | 20.8 |
| Centimeters                                    | 51.5     | 53.5 | 56.0              | 57.0 | 58.0 | 49.2      | 52.8 |
| 3. Stem extension (45° rise)                   |          |      |                   |      |      |           |      |
| Millimeters                                    | 100      | 100  | 100               | 100  | 100  | 100       | 100  |
| 4. Reach (top tube + stem reach)               |          |      |                   |      |      |           |      |
| Inches                                         | 22.1     | 22.9 | 23.9              | 24.3 | 24.7 | 21.2      | 22.6 |
| Centimeters                                    | 56.2     | 58.2 | 60.7              | 61.7 | 62.7 | 53.9      | 57.5 |
| 5. Handlebar width (25.4 mm diameter, 6° bend) |          |      |                   |      |      |           |      |
| Millimeters                                    | 560      | 560  | 560               | 560  | 560  | 610       | 610  |
| 6. Crank arm length                            |          |      |                   |      |      |           |      |
| Millimeters                                    | 170      | 170  | 170               | 170  | 170  | 170       | 170  |
| 7. Steerer length, threaded                    |          |      |                   |      |      |           |      |
| Inches                                         | 4.9      | 4.9  | 4.9               | 6.1  | 8.1  | 5.7       | 6.5  |
| Millimeters                                    | 125      | 125  | 125               | 155  | 205  | 145       | 165  |
| 8. Head tube length                            |          |      |                   |      |      |           |      |
| Inches                                         | 3.3      | 3.3  | 3.3               | 4.5  | 6.5  | 4.1       | 4.9  |
| Millimeters                                    | 85       | 85   | 85                | 115  | 165  | 105       | 125  |
| 9. Seatpost length (27.2 mm diameter)          |          |      |                   |      |      |           |      |
| Millimeters                                    | 300      | 300  | 300               | 300  | 300  | 300       | 300  |
| 10. Gearing                                    | 28/38/48 |      | 14-16-18-21-24-28 |      |      |           |      |

## General Information

|                  |                            |
|------------------|----------------------------|
| Hubset, Type     | HyperGlide                 |
| Spoke number     | 36                         |
| Spokes, Front    | 265 14 ga.                 |
| Rear(D/ND)       | 262/264 14 ga.             |
| Tire Size        | 26x1.95                    |
| Front Derailleur | 26.8 mm/1 <sup>1/8</sup> " |
| Bottom bracket   | BB-CS11                    |
| Shell Width      | 68                         |
| Axle length      | 127.5                      |
| R. dropout width | 135 mm                     |
| Headset size     | 22.2/30.2/26.4             |
| Weight           | 28.8 lb/13.1 kg.           |

## Upgrades

- Cartridge bottom bracket
- Front and rear quick release wheels
- Shimano M-System brakes
- Wide ratio 18 speed gearing for easy pedalling
- Trek saddle with hi-rise bar and stem for comfort
- Connection tires feature aggressive tread with connected center ridge

## Model 820

| Sizes                                          | 14.5     | 16   | 18                   | 20   | 22   | 14/24 17W | 20W  |
|------------------------------------------------|----------|------|----------------------|------|------|-----------|------|
| 1. Stand-over height                           |          |      |                      |      |      |           |      |
| Inches                                         | 27.5     | 28.4 | 29.3                 | 30.8 | 32.7 | 26.6      | NA   |
| Centimeters                                    | 69.8     | 72.0 | 74.3                 | 78.2 | 83.0 | 67.5      | NA   |
| 2. Top tube                                    |          |      |                      |      |      |           |      |
| Inches                                         | 20.3     | 21.1 | 22.1                 | 22.4 | 22.8 | 19.4      | 20.8 |
| Centimeters                                    | 51.5     | 53.5 | 56.0                 | 57.0 | 58.0 | 49.2      | 52.8 |
| 3. Stem extension (45° rise)                   |          |      |                      |      |      |           |      |
| Millimeters                                    | 100      | 100  | 100                  | 100  | 100  | 100       | 100  |
| 4. Reach (top tube + stem reach)               |          |      |                      |      |      |           |      |
| Inches                                         | 22.1     | 22.9 | 23.9                 | 24.3 | 24.7 | 21.2      | 22.6 |
| Centimeters                                    | 56.2     | 58.2 | 60.7                 | 61.7 | 62.7 | 53.9      | 57.5 |
| 5. Handlebar width (25.4 mm diameter, 6° bend) |          |      |                      |      |      |           |      |
| Millimeters                                    | 560      | 560  | 560                  | 560  | 560  | 610       | 610  |
| 6. Crank arm length                            |          |      |                      |      |      |           |      |
| Millimeters                                    | 170      | 170  | 170                  | 170  | 170  | 170       | 170  |
| 7. Steerer length, threaded                    |          |      |                      |      |      |           |      |
| Inches                                         | 4.9      | 4.9  | 4.9                  | 6.1  | 8.1  | 5.7       | 6.5  |
| Millimeters                                    | 125      | 125  | 125                  | 155  | 205  | 145       | 165  |
| 8. Head tube length                            |          |      |                      |      |      |           |      |
| Inches                                         | 3.3      | 3.3  | 3.3                  | 4.5  | 6.5  | 4.1       | 4.9  |
| Millimeters                                    | 85       | 85   | 85                   | 115  | 165  | 105       | 125  |
| 9. Seatpost length (27.2 mm diameter)          |          |      |                      |      |      |           |      |
| Millimeters                                    | 300      | 300  | 300                  | 300  | 300  | 300       | 300  |
| 10. Gearing                                    | 28/38/48 |      | 12-14-16-18-21-24-28 |      |      |           |      |

## General Information

|                  |                            |
|------------------|----------------------------|
| Hubset, Type     | HyperGlide                 |
| Spoke number     | 36                         |
| Spokes, Front    | 263 14 ga.                 |
| Rear(D/ND)       | 260/262 14 ga.             |
| Tire Size        | 26x1.95                    |
| Front Derailleur | 26.8 mm/1 <sup>1/8</sup> " |
| Bottom bracket   | BB-CS11                    |
| Shell Width      | 68                         |
| Axle length      | 127.5                      |
| R. dropout width | 135 mm                     |
| Headset size     | 22.2/30.2/26.4             |
| Weight           | 28.8 lb/13.1 kg.           |

## Upgrades

- Cro-Moly fork
- RapidFire Plus shifting with dial indicator
- 21 speed gearing
- System 1 Gel Lite saddle
- Connection tires are wide for comfort and stability
- Cassette type rear hub
- C-20 group



## Model 830

| Sizes                                          | 14.5     | 16     | 18                   | 20     | 22    |
|------------------------------------------------|----------|--------|----------------------|--------|-------|
| 1. Stand-over height                           |          |        |                      |        |       |
| Inches                                         | 27.5     | 28.4   | 29.3                 | 30.8   | 32.7  |
| Centimeters                                    | 69.8     | 72.0   | 74.3                 | 78.2   | 83.0  |
| 2. Top tube                                    |          |        |                      |        |       |
| Inches                                         | 20.3     | 21.1   | 22.1                 | 22.6   | 23.0  |
| Centimeters                                    | 51.5     | 53.5   | 56.0                 | 57.5   | 58.5  |
| 3. Stem extension/degrees rise                 |          |        |                      |        |       |
| Millimeters                                    | 105/15   | 105/15 | 120/15               | 135/15 | 150/5 |
| 4. Reach (top tube + stem reach)               |          |        |                      |        |       |
| Inches                                         | 23.8     | 24.6   | 26.1                 | 27.1   | 28.5  |
| Centimeters                                    | 60.4     | 62.4   | 66.2                 | 68.9   | 72.4  |
| 5. Handlebar width (25.4 mm diameter, 6° bend) |          |        |                      |        |       |
| Millimeters                                    | 560      | 560    | 560                  | 560    | 560   |
| 6. Crank Arm length                            |          |        |                      |        |       |
| Millimeters                                    | 170      | 170    | 170                  | 175    | 175   |
| 7. Steerer length, OS, threaded                |          |        |                      |        |       |
| Inches                                         | 4.7      | 4.7    | 4.7                  | 5.9    | 7.9   |
| Millimeters                                    | 120      | 120    | 120                  | 150    | 200   |
| 8. Head tube length                            |          |        |                      |        |       |
| Inches                                         | 3.3      | 3.3    | 3.3                  | 4.5    | 6.5   |
| Millimeters                                    | 85       | 85     | 85                   | 115    | 165   |
| 9. Seatpost length (27.2 mm diameter)          |          |        |                      |        |       |
| Millimeters                                    | 300      | 300    | 300                  | 300    | 300   |
| 10. Gearing                                    | 28/38/48 |        | 12-14-16-18-21-24-28 |        |       |

## General Information

|                  |                                         |
|------------------|-----------------------------------------|
| Hubset, Type     | HyperGlide                              |
| Spoke number     | 36                                      |
| Spokes, Front    | 263 14 ga.                              |
| Rear (D/ND)      | 260/262 14 ga.                          |
| Tire Size        | 26x2.0                                  |
| Front Derailleur | 31.7 mm/1 <sup>1</sup> / <sub>4</sub> " |
| Bottom bracket   | BB-LP20                                 |
| Shell Width      | 68                                      |
| Axle length      | 127.5                                   |
| R. dropout width | 135 mm                                  |
| Headset size     | 25.4/34.0/30.0                          |
| Weight           | 28.5 lb/13.0 kg.                        |

## Upgrades

- Full Tange OS double butted Cro-Moly frame
- Trek Cruise Control 3 Cro-Moly fork
- Top pull front derailleur with TripleTech cable routing
- Trek Cliffhanger/Cliffclimber 26x2.0 tire system
- System 1 Gel Lite saddle
- A-20 group, RapidFire Plus

## Model 850SHX

| Sizes                                          | 14.5     | 16    | 18                   | 20    |
|------------------------------------------------|----------|-------|----------------------|-------|
| 1. Stand-over height                           |          |       |                      |       |
| Inches                                         | 27.5     | 28.4  | 29.3                 | 30.8  |
| Centimeters                                    | 69.8     | 72.0  | 74.3                 | 78.2  |
| 2. Top tube                                    |          |       |                      |       |
| Inches                                         | 20.3     | 21.1  | 22.1                 | 22.6  |
| Centimeters                                    | 51.5     | 53.5  | 56.0                 | 57.5  |
| 3. Stem extension/degrees rise                 |          |       |                      |       |
| Millimeters                                    | 105/7    | 120/7 | 135/7                | 135/7 |
| 4. Reach (top tube + stem reach)               |          |       |                      |       |
| Inches                                         | 24.1     | 25.4  | 27.0                 | 27.6  |
| Centimeters                                    | 61.2     | 64.6  | 68.5                 | 70.0  |
| 5. Handlebar width (25.4 mm diameter, 6° bend) |          |       |                      |       |
| Millimeters                                    | 560      | 560   | 560                  | 560   |
| 6. Crank arm length                            |          |       |                      |       |
| Millimeters                                    | 175      | 175   | 175                  | 175   |
| 7. Steerer length, OS, threaded                |          |       |                      |       |
| Inches                                         | 4.7      | 4.7   | 4.7                  | 5.9   |
| Millimeters                                    | 120      | 120   | 120                  | 150   |
| 8. Head tube length                            |          |       |                      |       |
| Inches                                         | 3.3      | 3.3   | 3.3                  | 4.5   |
| Millimeters                                    | 85       | 85    | 85                   | 115   |
| 9. Seatpost length (27.2 mm diameter)          |          |       |                      |       |
| Millimeters                                    | 300      | 300   | 300                  | 300   |
| 10. Gearing                                    | 28/38/48 |       | 12-14-16-18-21-24-28 |       |

## General Information

|                  |                                         |
|------------------|-----------------------------------------|
| Hubset, Type     | HyperGlide                              |
| Spoke number     | 36                                      |
| Spokes, Front    | 263 14 ga.                              |
| Rear (D/ND)      | 260/262 14 ga.                          |
| Tire Size        | 26x2.0                                  |
| Front Derailleur | 31.7 mm/1 <sup>1</sup> / <sub>4</sub> " |
| Bottom bracket   | BB-LP20                                 |
| Shell Width      | 68                                      |
| Axle length      | 127.5                                   |
| R. dropout width | 135 mm                                  |
| Headset size     | 25.4/34.0/30.0                          |
| Weight           | 29.9 lb/13.6 kg.                        |

## Upgrades

- True Temper OX double butted Cro-Moly frame
- SR DuoTrack spring/elastomer suspension fork
- Toe clips and straps
- Low rise stem designed for positioning with suspension fork
- System 1 QR seat clamp



## Model 930

| Sizes                                           | 15       | 16.5  | 18                   | 20     | 22     |
|-------------------------------------------------|----------|-------|----------------------|--------|--------|
| 1. Stand-over height                            |          |       |                      |        |        |
| Inches                                          | 27.9     | 28.7  | 29.6                 | 30.8   | 32.4   |
| Centimeters                                     | 71.0     | 73.0  | 75.1                 | 78.1   | 82.3   |
| 2. Top tube                                     |          |       |                      |        |        |
| Inches                                          | 20.3     | 21.2  | 22.2                 | 22.6   | 23.0   |
| Centimeters                                     | 51.5     | 53.9  | 56.5                 | 57.5   | 58.5   |
| 3. Stem extension (standard type, degrees rise) |          |       |                      |        |        |
| Millimeters                                     | 105/5    | 120/5 | 135/10               | 135/10 | 150/10 |
| 4. Reach (top tube + stem reach)                |          |       |                      |        |        |
| Inches                                          | 24.1     | 25.6  | 27.0                 | 27.4   | 28.3   |
| Centimeters                                     | 61.2     | 65.0  | 68.5                 | 69.5   | 71.9   |
| 5. Handlebar width (25.4 mm diameter, 5° bend)  |          |       |                      |        |        |
| Millimeters                                     | 560      | 560   | 560                  | 560    | 560    |
| 6. Crank arm length                             |          |       |                      |        |        |
| Millimeters                                     | 170      | 175   | 175                  | 175    | 175    |
| 7. Steerer length, OS, threaded                 |          |       |                      |        |        |
| Inches                                          | 5.9      | 5.9   | 5.9                  | 6.4    | 7.9    |
| Millimeters                                     | 149      | 149   | 149                  | 162    | 200    |
| 8. Head tube length                             |          |       |                      |        |        |
| Inches                                          | 4.3      | 4.3   | 4.3                  | 4.8    | 6.3    |
| Millimeters                                     | 110      | 110   | 110                  | 123    | 159    |
| 9. Seatpost length (27.2 mm diameter)           |          |       |                      |        |        |
| Millimeters                                     | 300      | 300   | 300                  | 300    | 300    |
| 10. Gearing                                     | 26/36/46 |       | 13-15-17-20-23-26-30 |        |        |

### General Information

|                  |                  |
|------------------|------------------|
| Hubset, Type     | HyperGlide       |
| Spoke number     | 32               |
| Spokes, Front    | 268 14 ga.       |
| Rear(D/ND)       | 266/267 14 ga.   |
| Tire Size        | 26x2.1           |
| Front Derailleur | 31.7 mm/1 1/4"   |
| Bottom bracket   | BB-LP30          |
| Shell Width      | 73               |
| Axle length      | 118              |
| R. dropout width | 135 mm           |
| Headset size     | 25.4/34.0/30.0   |
| Weight           | 28.3 lb/12.9 kg. |

### Upgrades

- True Temper OX Comp II Cro-Moly frame, low temperature brazed
- Matrix Single Track Comp rims
- Trek Z-Axis tire system, 26x2.1, and stainless steel spokes
- System 1 pedals and alloy bars (220 gm)
- System 2 Gel Lite saddle

## Model 930SHX

| Sizes                                          | 16.5     | 18   | 20                   |
|------------------------------------------------|----------|------|----------------------|
| 1. Stand-over height                           |          |      |                      |
| Inches                                         | 28.7     | 29.6 | 30.8                 |
| Centimeters                                    | 73.0     | 75.1 | 78.1                 |
| 2. Top tube                                    |          |      |                      |
| Inches                                         | 21.2     | 22.2 | 22.6                 |
| Centimeters                                    | 53.9     | 56.5 | 57.5                 |
| 3. Stem extension (Direct Connect, 7° drop)    |          |      |                      |
| Millimeters                                    | 120      | 135  | 135                  |
| 4. Reach (top tube + stem reach)               |          |      |                      |
| Inches                                         | 25.9     | 26.9 | 27.9                 |
| Centimeters                                    | 65.7     | 68.3 | 70.8                 |
| 5. Handlebar width (25.4 mm diameter, 5° bend) |          |      |                      |
| Millimeters                                    | 560      | 560  | 560                  |
| 6. Crank arm length                            |          |      |                      |
| Millimeters                                    | 175      | 175  | 175                  |
| 7. Steerer length, OS, non-threaded            |          |      |                      |
| Inches                                         | 7.5      | 7.5  | 8.0                  |
| Millimeters                                    | 190      | 190  | 202                  |
| 8. Head tube length                            |          |      |                      |
| Inches                                         | 4.3      | 4.3  | 4.8                  |
| Millimeters                                    | 110      | 110  | 123                  |
| 9. Seatpost length (27.2 mm diameter)          |          |      |                      |
| Millimeters                                    | 300      | 300  | 300                  |
| 10. Gearing                                    | 26/36/46 |      | 13-15-17-20-23-26-30 |

### General Information

|                  |                  |
|------------------|------------------|
| Hubset, Type     | HyperGlide       |
| Spoke number     | 32               |
| Spokes, Front    | 268 14 ga.       |
| Rear(D/ND)       | 266/267 14 ga.   |
| Tire Size        | 26x2.1           |
| Front Derailleur | 31.7 mm/1 1/4"   |
| Bottom bracket   | BB-LP30          |
| Shell Width      | 73               |
| Axle length      | 118              |
| R. dropout width | 135 mm           |
| Headset size     | 25.4/34.0/30.0   |
| Weight           | 29.4 lb/13.4 kg. |

### Upgrades

- Trek Shock Wave elastomer suspension fork
- AheadSet
- System 2 TIG Cro-Moly direct connect stem
- System 1 bar-ends



## Model 950

| Sizes                                           | 15       | 16.5  | 18                   | 20     | 22     |
|-------------------------------------------------|----------|-------|----------------------|--------|--------|
| 1. Stand-over height                            |          |       |                      |        |        |
| Inches                                          | 27.9     | 28.7  | 29.6                 | 30.8   | 32.4   |
| Centimeters                                     | 71.0     | 73.0  | 75.1                 | 78.1   | 82.3   |
| 2. Top tube                                     |          |       |                      |        |        |
| Inches                                          | 20.3     | 21.2  | 22.2                 | 22.6   | 23.0   |
| Centimeters                                     | 51.5     | 53.9  | 56.5                 | 57.5   | 58.5   |
| 3. Stem extension (standard type, degrees rise) |          |       |                      |        |        |
| Millimeters                                     | 105/5    | 120/5 | 135/10               | 135/10 | 150/10 |
| 4. Reach (top tube + stem reach)                |          |       |                      |        |        |
| Inches                                          | 24.1     | 25.6  | 27.0                 | 27.4   | 28.3   |
| Centimeters                                     | 61.2     | 65.0  | 68.5                 | 69.5   | 71.9   |
| 5. Handlebar width (25.4 mm diameter, 5° bend)  |          |       |                      |        |        |
| Millimeters                                     | 560      | 560   | 560                  | 560    | 560    |
| 6. Crank arm length                             |          |       |                      |        |        |
| Millimeters                                     | 170      | 175   | 175                  | 175    | 175    |
| 7. Steerer length, OS, threaded                 |          |       |                      |        |        |
| Inches                                          | 5.9      | 5.9   | 5.9                  | 6.4    | 7.9    |
| Millimeters                                     | 149      | 149   | 149                  | 162    | 200    |
| 8. Head tube length                             |          |       |                      |        |        |
| Inches                                          | 4.3      | 4.3   | 4.3                  | 4.8    | 6.3    |
| Millimeters                                     | 110      | 110   | 110                  | 123    | 159    |
| 9. Seatpost length (27.2 mm diameter)           |          |       |                      |        |        |
| Millimeters                                     | 300      | 300   | 300                  | 300    | 300    |
| 10. Gearing                                     | 26/36/46 |       | 13-15-17-20-23-26-30 |        |        |

### General Information

|                  |                            |
|------------------|----------------------------|
| Hubset, Type     | HyperGlide                 |
| Spoke number     | 32                         |
| Spokes, Front    | 268 14 ga.                 |
| Rear(D/ND)       | 266/267 14 ga.             |
| Tire Size        | 26x2.1                     |
| Front Derailleur | 31.7 mm/1 <sup>1/4</sup> " |
| Bottom bracket   | BB-UN51                    |
| Shell Width      | 73                         |
| Axle length      | 118                        |
| R. dropout width | 135 mm                     |
| Headset size     | 25.4/34.0/30.0             |
| Weight           | 27.2 lb/12.4 kg.           |

### Upgrades

- System 1 butted Cro-Moly fork
- New Deore LX group
- Deore XT rear derailleur
- System 2 alloy handlebars (170 gm)
- System 2 wide racing saddle

## Model 970

| Sizes                                          | 15       | 16.5 | 18                   | 20   | 22   |
|------------------------------------------------|----------|------|----------------------|------|------|
| 1. Stand-over height                           |          |      |                      |      |      |
| Inches                                         | 27.9     | 28.7 | 29.6                 | 30.8 | 32.4 |
| Centimeters                                    | 71.0     | 73.0 | 75.1                 | 78.1 | 82.3 |
| 2. Top tube                                    |          |      |                      |      |      |
| Inches                                         | 20.3     | 21.2 | 22.2                 | 22.6 | 23.0 |
| Centimeters                                    | 51.5     | 53.9 | 56.5                 | 57.5 | 58.5 |
| 3. Stem extension (Direct Connect, 7° rise)    |          |      |                      |      |      |
| Millimeters                                    | 105      | 120  | 135                  | 135  | 135  |
| 4. Reach (top tube + stem reach)               |          |      |                      |      |      |
| Inches                                         | 24.1     | 25.6 | 27.1                 | 27.5 | 27.9 |
| Centimeters                                    | 61.1     | 64.9 | 68.8                 | 69.8 | 70.8 |
| 5. Handlebar width (25.4 mm diameter, 5° bend) |          |      |                      |      |      |
| Millimeters                                    | 560      | 560  | 560                  | 560  | 560  |
| 6. Crank arm length                            |          |      |                      |      |      |
| Millimeters                                    | 175      | 175  | 175                  | 175  | 175  |
| 7. Steerer length, OS, non-threaded            |          |      |                      |      |      |
| Inches                                         | 7.8      | 7.8  | 7.8                  | 8.3  | 9.8  |
| Millimeters                                    | 199      | 199  | 199                  | 212  | 248  |
| 8. Head tube length                            |          |      |                      |      |      |
| Inches                                         | 4.3      | 4.3  | 4.3                  | 4.8  | 6.3  |
| Millimeters                                    | 110      | 110  | 110                  | 123  | 159  |
| 9. Seatpost length (27.2 mm diameter)          |          |      |                      |      |      |
| Millimeters                                    | 300      | 300  | 350                  | 350  | 350  |
| 10. Gearing                                    | 26/36/46 |      | 13-15-17-20-23-26-30 |      |      |

### General Information

|                  |                            |
|------------------|----------------------------|
| Hubset, Type     | HyperGlide                 |
| Spoke number     | 32                         |
| Spokes, Front    | 268 14/15ga.               |
| Rear(D/ND)       | 266/267 14/15ga.           |
| Tire Size        | 26x2.1                     |
| Front Derailleur | 31.7 mm/1 <sup>1/4</sup> " |
| Bottom bracket   | BB-UN51                    |
| Shell Width      | 73                         |
| Axle length      | 122.5                      |
| R. dropout width | 135 mm                     |
| Headset size     | 25.4/34.0/30.0             |
| Weight           | 26.8 lb/12.2 kg.           |

### Upgrades

- System 2 butted Cro-Moly fork
- Deore DX group with XT front and rear derailleurs
- System 3 alloy bars (150 gm), wide racing saddle with leather cover, hollow Cro-Moly rails
- Matrix Single Track Pro rims, 14/15 butted spokes, and Control Track tire system





## Model 7000

| Sizes                                          | 15       | 16.5 | 18                   | 20   | 22   |
|------------------------------------------------|----------|------|----------------------|------|------|
| 1. Stand-over height                           |          |      |                      |      |      |
| Inches                                         | 28.0     | 28.7 | 29.6                 | 30.7 | 32.4 |
| Centimeters                                    | 71.0     | 73.0 | 75.1                 | 78.1 | 82.3 |
| 2. Top tube                                    |          |      |                      |      |      |
| Inches                                         | 20.7     | 21.7 | 21.9                 | 22.6 | 23.0 |
| Centimeters                                    | 52.5     | 55.0 | 56.6                 | 57.4 | 58.5 |
| 3. Stem extension (Direct Connect, 7° rise)    |          |      |                      |      |      |
| Millimeters                                    | 105      | 120  | 135                  | 135  | 150  |
| 4. Reach (top tube + stem reach)               |          |      |                      |      |      |
| Inches                                         | 24.4     | 26.0 | 27.1                 | 27.4 | 28.4 |
| Centimeters                                    | 62.1     | 66.0 | 68.9                 | 69.7 | 72.2 |
| 5. Handlebar width (25.4 mm diameter, 5° bend) |          |      |                      |      |      |
| Millimeters                                    | 560      | 560  | 560                  | 560  | 560  |
| 6. Crank arm length                            |          |      |                      |      |      |
| Millimeters                                    | 170      | 175  | 175                  | 175  | 175  |
| 7. Steerer length, OS, non-threaded            |          |      |                      |      |      |
| Inches                                         | 7.2      | 7.2  | 7.2                  | 8.1  | 10.2 |
| Millimeters                                    | 182      | 182  | 182                  | 205  | 258  |
| 8. Head tube length                            |          |      |                      |      |      |
| Inches                                         | 3.7      | 3.7  | 3.7                  | 4.6  | 6.6  |
| Millimeters                                    | 94       | 94   | 94                   | 117  | 168  |
| 9. Seatpost length (27.2 mm diameter)          |          |      |                      |      |      |
|                                                | 300      | 300  | 300                  | 300  | 300  |
| 10. Gearing                                    | 26/36/46 |      | 13-15-17-20-23-26-30 |      |      |

## General Information

|                  |                  |
|------------------|------------------|
| Hubset, Type     | HyperGlide       |
| Spoke number     | 32               |
| Spokes, Front    | 268 14 ga.       |
| Rear(D/ND)       | 266/267 14 ga.   |
| Tire Size        | 26x2.1           |
| Front Derailleur | 34.9 mm/1 3/8"   |
| Bottom bracket   | BB-LP30          |
| Shell Width      | 68               |
| Axle length      | 118              |
| R. dropout width | 135 mm           |
| Headset size     | 25.4/34.0/30.0   |
| Weight           | 25.7 lb/11.7 kg. |

## Upgrades

- Easton E9 Program aluminum tubing
- System 1 butted Cro-Moly fork
- New Deore LX derailleurs
- AheadSet with System 2 direct connect stem
- System 2 bars, seatpost, and wide racing saddle



## Model 8000

| Sizes                                          | 15       | 16.5 | 18                   | 20   | 22   |
|------------------------------------------------|----------|------|----------------------|------|------|
| 1. Stand-over height                           |          |      |                      |      |      |
| Inches                                         | 28.0     | 28.7 | 29.6                 | 30.7 | 32.4 |
| Centimeters                                    | 71.0     | 73.0 | 75.1                 | 78.1 | 82.3 |
| 2. Top tube                                    |          |      |                      |      |      |
| Inches                                         | 20.7     | 21.7 | 21.9                 | 22.6 | 23.0 |
| Centimeters                                    | 52.5     | 55.0 | 56.6                 | 57.4 | 58.5 |
| 3. Stem extension (Direct Connect, 7° rise)    |          |      |                      |      |      |
| Millimeters                                    | 105      | 120  | 135                  | 135  | 150  |
| 4. Reach (top tube + stem reach)               |          |      |                      |      |      |
| Inches                                         | 24.4     | 26.0 | 27.1                 | 27.4 | 28.4 |
| Centimeters                                    | 62.1     | 66.0 | 68.9                 | 69.7 | 72.2 |
| 5. Handlebar width (25.4 mm diameter, 5° bend) |          |      |                      |      |      |
| Millimeters                                    | 560      | 560  | 560                  | 560  | 560  |
| 6. Crank arm length                            |          |      |                      |      |      |
| Millimeters                                    | 170      | 175  | 175                  | 175  | 175  |
| 7. Steerer length, OS, non-threaded            |          |      |                      |      |      |
| Inches                                         | 7.2      | 7.2  | 7.2                  | 8.1  | 10.2 |
| Millimeters                                    | 182      | 182  | 182                  | 205  | 258  |
| 8. Head tube length                            |          |      |                      |      |      |
| Inches                                         | 3.7      | 3.7  | 3.7                  | 4.6  | 6.6  |
| Millimeters                                    | 94       | 94   | 94                   | 117  | 168  |
| 9. Seatpost length (27.2 mm diameter)          |          |      |                      |      |      |
| Millimeters                                    | 300      | 300  | 350                  | 350  | 350  |
| 10. Gearing                                    | 26/36/46 |      | 13-15-17-20-23-26-30 |      |      |

### General Information

|                  |                            |
|------------------|----------------------------|
| Hubset, Type     | HyperGlide                 |
| Spoke number     | 32                         |
| Spokes, Front    | 268 14/15ga.               |
| Rear(D/ND)       | 266/267 14/15ga.           |
| Tire Size        | 26x2.1                     |
| Front Derailleur | 34.9 mm/1 <sup>3/8</sup> " |
| Bottom bracket   | BB-UN51                    |
| Shell Width      | 68                         |
| Axle length      | 118                        |
| R. dropout width | 135 mm                     |
| Headset size     | 25.4/34.0/30.0             |
| Weight           | 25.2 lb/11.5 kg.           |

### Upgrades

- System 2 butted Cro-Moly fork
- New Deore LX group with XT rear derailleur
- Matrix Single Track Pro rims and Control Track tire system
- 14/15 butted stainless steel spokes
- System 2 pedals

## Model 8000SHX

| Sizes                                          | 15       | 16.5 | 18                   | 20   |
|------------------------------------------------|----------|------|----------------------|------|
| 1. Stand-over height                           |          |      |                      |      |
| Inches                                         | 28.0     | 28.7 | 29.6                 | 30.7 |
| Centimeters                                    | 71.0     | 73.0 | 75.1                 | 78.1 |
| 2. Top tube                                    |          |      |                      |      |
| Inches                                         | 20.7     | 21.7 | 21.9                 | 22.6 |
| Centimeters                                    | 52.5     | 55.0 | 56.6                 | 57.4 |
| 3. Stem extension (Direct Connect, 7° drop)    |          |      |                      |      |
| Millimeters                                    | 105      | 120  | 135                  | 135  |
| 4. Reach (top tube + stem reach)               |          |      |                      |      |
| Inches                                         | 24.7     | 26.3 | 27.5                 | 27.8 |
| Centimeters                                    | 62.8     | 66.8 | 69.9                 | 70.7 |
| 5. Handlebar width (25.4 mm diameter, 5° bend) |          |      |                      |      |
| Millimeters                                    | 560      | 560  | 560                  | 560  |
| 6. Crank arm length                            |          |      |                      |      |
| Millimeters                                    | 170      | 175  | 175                  | 175  |
| 7. Steerer length, OS, non-threaded            |          |      |                      |      |
| Inches                                         | 6.8      | 6.8  | 6.8                  | 7.7  |
| Millimeters                                    | 173      | 173  | 173                  | 196  |
| 8. Head tube length                            |          |      |                      |      |
| Inches                                         | 3.7      | 3.7  | 3.7                  | 4.6  |
| Millimeters                                    | 94       | 94   | 94                   | 117  |
| 9. Seatpost length (27.2 mm diameter)          |          |      |                      |      |
| Millimeters                                    | 300      | 300  | 350                  | 350  |
| 10. Gearing                                    | 26/36/46 |      | 13-15-17-20-23-26-30 |      |

### General Information

|                  |                            |
|------------------|----------------------------|
| Hubset, Type     | HyperGlide                 |
| Spoke number     | 32                         |
| Spokes, Front    | 268 14/15ga.               |
| Rear(D/ND)       | 266/267 14/15ga.           |
| Tire Size        | 26x2.1                     |
| Front Derailleur | 34.9 mm/1 <sup>3/8</sup> " |
| Bottom bracket   | BB-UN51                    |
| Shell Width      | 68                         |
| Axle length      | 118                        |
| R. dropout width | 135 mm                     |
| Headset size     | 25.4/34.0/30.0             |
| Weight           | 27.4 lb/12.5 kg.           |

### Upgrades

- Trek Mogul fork
- Air/oil suspension with easily adjustable preload
- System 2 bonded alloy bar-ends



## Model 8300

| Sizes                                          | 15       | 16.5 | 18                      | 20   | 22   |
|------------------------------------------------|----------|------|-------------------------|------|------|
| 1. Stand-over height                           |          |      |                         |      |      |
| Inches                                         | 28.0     | 28.7 | 29.6                    | 30.7 | 32.4 |
| Centimeters                                    | 71.0     | 73.0 | 75.1                    | 78.1 | 82.3 |
| 2. Top tube                                    |          |      |                         |      |      |
| Inches                                         | 20.7     | 21.7 | 21.9                    | 22.6 | 23.0 |
| Centimeters                                    | 52.5     | 55.0 | 56.6                    | 57.4 | 58.5 |
| 3. Stem extension (Direct Connect, 7° rise)    |          |      |                         |      |      |
| Millimeters                                    | 105      | 120  | 135                     | 135  | 150  |
| 4. Reach (top tube + stem reach)               |          |      |                         |      |      |
| Inches                                         | 24.4     | 26.0 | 27.1                    | 27.4 | 28.4 |
| Centimeters                                    | 62.1     | 66.0 | 68.9                    | 69.7 | 72.2 |
| 5. Handlebar width (25.4 mm diameter, 5° bend) |          |      |                         |      |      |
| Millimeters                                    | 560      | 560  | 560                     | 560  | 560  |
| 6. Crank arm length                            |          |      |                         |      |      |
| Millimeters                                    | 175      | 175  | 175                     | 175  | 175  |
| 7. Steerer length, OS, non-threaded            |          |      |                         |      |      |
| Inches                                         | 7.2      | 7.2  | 7.2                     | 8.1  | 10.2 |
| Millimeters                                    | 182      | 182  | 182                     | 205  | 258  |
| 8. Head tube length                            |          |      |                         |      |      |
| Inches                                         | 3.7      | 3.7  | 3.7                     | 4.6  | 6.6  |
| Millimeters                                    | 94       | 94   | 94                      | 117  | 168  |
| 9. Seatpost length (27.2 mm diameter)          |          |      |                         |      |      |
| Millimeters                                    | 300      | 300  | 350                     | 350  | 350  |
| 10. Gearing                                    | 20/32/42 |      | 11-12-14-16-18-21-24-28 |      |      |

### General Information

|                  |                                         |
|------------------|-----------------------------------------|
| Hubset, Type     | HyperGlide                              |
| Spoke number     | 32                                      |
| Spokes, Front    | 268 14/15ga.                            |
| Rear(D/ND)       | 266/267 14/15ga.                        |
| Tire Size        | 26x2.1                                  |
| Front Derailleur | 34.9 mm/1 <sup>3</sup> / <sub>8</sub> " |
| Bottom bracket   | BB-UN51                                 |
| Shell Width      | 68                                      |
| Axle length      | 118                                     |
| R. dropout width | 135 mm                                  |
| Headset size     | 25.4/34.0/30.0                          |
| Weight           | 24.3 lb/11.0 kg.                        |

### Upgrades

- Carbon fiber composite frame
- System 3 butted Cro-Moly fork
- Suntour Micro-Drive components
- System 3 handlebars (150 gm)
- Top mount shifters

## Model 8700

| Sizes                                          | 15       | 16.5 | 18                   | 20   | 22   |
|------------------------------------------------|----------|------|----------------------|------|------|
| 1. Stand-over height                           |          |      |                      |      |      |
| Inches                                         | 28.0     | 28.7 | 29.6                 | 30.7 | 32.4 |
| Centimeters                                    | 71.0     | 73.0 | 75.1                 | 78.1 | 82.3 |
| 2. Top tube                                    |          |      |                      |      |      |
| Inches                                         | 20.7     | 21.7 | 21.9                 | 22.6 | 23.0 |
| Centimeters                                    | 52.5     | 55.0 | 56.6                 | 57.4 | 58.5 |
| 3. Stem extension (Direct Connect, 7° rise)    |          |      |                      |      |      |
| Millimeters                                    | 105      | 120  | 135                  | 135  | 150  |
| 4. Reach (top tube + stem reach)               |          |      |                      |      |      |
| Inches                                         | 24.4     | 26.0 | 27.1                 | 27.4 | 28.4 |
| Centimeters                                    | 62.1     | 66.0 | 68.9                 | 69.7 | 72.2 |
| 5. Handlebar width (25.4 mm diameter, 5° bend) |          |      |                      |      |      |
| Millimeters                                    | 560      | 560  | 560                  | 560  | 560  |
| 6. Crank arm length                            |          |      |                      |      |      |
| Millimeters                                    | 170      | 175  | 175                  | 175  | 175  |
| 7. Steerer length, OS, non-threaded            |          |      |                      |      |      |
| Inches                                         | 7.2      | 7.2  | 7.2                  | 8.1  | 10.2 |
| Millimeters                                    | 182      | 182  | 182                  | 205  | 258  |
| 8. Head tube length                            |          |      |                      |      |      |
| Inches                                         | 3.7      | 3.7  | 3.7                  | 4.6  | 6.6  |
| Millimeters                                    | 94       | 94   | 94                   | 117  | 168  |
| 9. Seatpost length (27.2 mm diameter)          |          |      |                      |      |      |
| Millimeters                                    | 300      | 300  | 350                  | 350  | 350  |
| 10. Gearing                                    | 26/36/46 |      | 13-15-17-20-23-26-30 |      |      |

### General Information

|                  |                                         |
|------------------|-----------------------------------------|
| Hubset, Type     | HyperGlide                              |
| Spoke number     | 32                                      |
| Spokes, Front    | 268 14/15ga.                            |
| Rear(D/ND)       | 266/267 14/15ga.                        |
| Tire Size        | 26x2.1                                  |
| Front Derailleur | 34.9 mm/1 <sup>3</sup> / <sub>8</sub> " |
| Bottom bracket   | BB-UN51                                 |
| Shell Width      | 68                                      |
| Axle length      | 127.5                                   |
| R. dropout width | 135 mm                                  |
| Headset size     | 25.4/34.0/30.0                          |
| Weight           | 24.5 lb/11.1 kg.                        |

### Upgrades

- Shimano DX group with XT front and rear derailleurs
- System 3 wide racing saddle w/leather cover and Cro-Moly rails
- Control Track Lite tires with Kevlar bead and low density rubber
- System 3 pedals, seatpost, and saddle





## Model 9000

| Sizes                                          | 16.5     | 18                   | 20   | 22   |
|------------------------------------------------|----------|----------------------|------|------|
| 1. Stand-over height                           |          |                      |      |      |
| Inches                                         | 29.5     | 30.4                 | 31.5 | 33.2 |
| Centimeters                                    | 74.9     | 77.2                 | 80.0 | 84.3 |
| 2. Top tube                                    |          |                      |      |      |
| Inches                                         | 21.3     | 21.8                 | 22.1 | 22.7 |
| Centimeters                                    | 54.1     | 55.4                 | 56.1 | 57.6 |
| 3. Stem extension (Direct Connect, 7° drop)    |          |                      |      |      |
| Millimeters                                    | 120      | 135                  | 150  | 150  |
| 4. Reach (top tube + stem reach)               |          |                      |      |      |
| Inches                                         | 25.9     | 27.0                 | 27.9 | 28.5 |
| Centimeters                                    | 65.8     | 68.6                 | 70.8 | 72.3 |
| 5. Handlebar width (25.4 mm diameter, 5° bend) |          |                      |      |      |
| Millimeters                                    | 560      | 560                  | 560  | 560  |
| 6. Crank arm length                            |          |                      |      |      |
| Millimeters                                    | 175      | 175                  | 175  | 175  |
| 7. Steerer length, OS, non-threaded            |          |                      |      |      |
| Inches                                         | 7.5      | 7.5                  | 8.0  | 9.4  |
| Millimeters                                    | 190      | 190                  | 203  | 239  |
| 8. Head tube length                            |          |                      |      |      |
| Inches                                         | 4.3      | 4.3                  | 4.8  | 6.3  |
| Millimeters                                    | 109      | 109                  | 122  | 160  |
| 9. Seatpost length (27.2 mm diameter)          |          |                      |      |      |
| Millimeters                                    | 250      | 300                  | 350  | 350  |
| 10. Gearing                                    | 26/36/46 | 13-15-17-20-23-26-30 |      |      |

## General Information

|                  |                                         |
|------------------|-----------------------------------------|
| Hubset, Type     | HyperGlide                              |
| Spoke number     | 32                                      |
| Spokes, Front    | 268 14/15ga.                            |
| Rear(D/ND)       | 266/267 14/15ga.                        |
| Tire Size        | 26x2.1                                  |
| Front Derailleur | 34.9 mm/1 <sup>3</sup> / <sub>8</sub> " |
| Bottom bracket   | BB-UN51                                 |
| Shell Width      | 73                                      |
| Axle length      | 118                                     |
| R. dropout width | 135 mm                                  |
| Headset size     | 25.4/34.0/30.0                          |
| Weight           | 28.8 lb/13.1 kg.                        |

## Upgrades

- Easton VariLite Program aluminum frame
- Mogul air/oil suspension fork
- AB Zorb II rear monoshock with adjustable rebound damping
- 6061 T6 aluminum swingarm
- New Deore LX group with XT rear derailleur



## Model 9200

| Sizes                                          | 16.5     | 18   | 20                   | 22   |
|------------------------------------------------|----------|------|----------------------|------|
| 1. Stand-over height                           |          |      |                      |      |
| Inches                                         | 29.5     | 30.4 | 31.5                 | 33.2 |
| Centimeters                                    | 74.9     | 77.2 | 80.0                 | 84.3 |
| 2. Top tube                                    |          |      |                      |      |
| Inches                                         | 21.3     | 21.8 | 22.1                 | 22.7 |
| Centimeters                                    | 54.1     | 55.4 | 56.1                 | 57.6 |
| 3. Stem extension (Direct Connect, 7° drop)    |          |      |                      |      |
| Millimeters                                    | 120      | 135  | 150                  | 150  |
| 4. Reach (top tube + stem reach)               |          |      |                      |      |
| Inches                                         | 25.9     | 27.0 | 27.9                 | 28.5 |
| Centimeters                                    | 65.8     | 68.6 | 70.8                 | 72.3 |
| 5. Handlebar width (25.4 mm diameter, 5° bend) |          |      |                      |      |
| Millimeters                                    | 560      | 560  | 560                  | 560  |
| 6. Crank arm length                            |          |      |                      |      |
| Millimeters                                    | 175      | 175  | 175                  | 175  |
| 7. Steerer length, OS, non-threaded            |          |      |                      |      |
| Inches                                         | 7.5      | 7.5  | 8.0                  | 9.4  |
| Millimeters                                    | 190      | 190  | 203                  | 239  |
| 8. Head tube length                            |          |      |                      |      |
| Inches                                         | 4.3      | 4.3  | 4.8                  | 6.3  |
| Millimeters                                    | 109      | 109  | 122                  | 160  |
| 9. Seatpost length (27.2 mm diameter)          |          |      |                      |      |
| Millimeters                                    | 250      | 300  | 350                  | 350  |
| 10. Gearing                                    | 26/36/46 |      | 13-15-17-20-23-26-30 |      |

### General Information

|                  |                            |
|------------------|----------------------------|
| Hubset, Type     | HyperGlide                 |
| Spoke number     | 32                         |
| Spokes, Front    | 269 14/15ga.               |
| Rear(D/ND)       | 268/269 14/15ga.           |
| Tire Size        | 26 x 2.1                   |
| Front Derailleur | 34.9 mm/1 <sup>3/8</sup> " |
| Bottom bracket   | BB-UN51                    |
| Shell Width      | 73                         |
| Axle length      | 122.5                      |
| R. dropout width | 135 mm                     |
| Headset size     | 25.4/34.0/30.0             |
| Weight           | 28.8 lb/13.1 kg.           |

### Upgrades

- Easton EA70 aluminum frame
- Mogul Black Diamond fork
- Deore DX group with XT front and rear derailleurs
- System 3 stem and bar-ends
- System 4 handlebars (130 gm)

## Model 9500

| Sizes                                          | 16.5     | 18    | 20                      | 22    |
|------------------------------------------------|----------|-------|-------------------------|-------|
| 1. Stand-over height                           |          |       |                         |       |
| Inches                                         | 29.5     | 30.4  | 31.5                    | 33.2  |
| Centimeters                                    | 74.9     | 77.2  | 80.0                    | 84.3  |
| 2. Top tube                                    |          |       |                         |       |
| Inches                                         | 21.3     | 21.8  | 22.1                    | 22.7  |
| Centimeters                                    | 54.1     | 55.4  | 56.1                    | 57.6  |
| 3. Stem extension (Direct Connect, 7° drop)    |          |       |                         |       |
| Millimeters                                    | 120      | 135   | 150                     | 150   |
| 4. Reach (top tube + stem reach)               |          |       |                         |       |
| Inches                                         | 25.9     | 27.0  | 27.9                    | 28.5  |
| Centimeters                                    | 65.8     | 68.6  | 70.8                    | 72.3  |
| 5. Handlebar width (25.4 mm diameter, 5° bend) |          |       |                         |       |
| Millimeters                                    | 560      | 560   | 560                     | 560   |
| 6. Crank arm length                            |          |       |                         |       |
| Millimeters                                    | 175      | 175   | 175                     | 175   |
| 7. Steerer length, OS, non-threaded            |          |       |                         |       |
| Inches                                         | 7.5      | 7.5   | 8.1                     | 9.5   |
| Millimeters                                    | 192.0    | 192.0 | 205.0                   | 241.0 |
| 8. Head tube length                            |          |       |                         |       |
| Inches                                         | 4.3      | 4.3   | 4.8                     | 6.3   |
| Millimeters                                    | 109      | 109   | 122                     | 160   |
| 9. Seatpost length (27.2 mm diameter)          |          |       |                         |       |
| Millimeters                                    | 250      | 300   | 350                     | 350   |
| 10. Gearing                                    | 26/36/46 |       | 12-13-14-16-18-21-24-28 |       |

### General Information

|                  |                  |
|------------------|------------------|
| Hubset, Type     | HyperGlide       |
| Spoke number     | 32               |
| Spokes, Front    | 269 14/15ga.     |
| Rear(D/ND)       | 268/269 14/15ga. |
| Tire Size        | 26x2.1           |
| Front Derailleur | 34.9             |
| Bottom bracket   | BB-91            |
| Shell Width      | 73               |
| Axle length      | 107              |
| R. dropout width | 135 mm           |
| Headset size     | 25.4/34.0/30.0   |
| Weight           | 27.6 lb/12.5 kg. |

### Upgrades

- OCLV carbon fiber composite swingarm
- Shimano XTR group with XTR SGS rear derailleur
- XT SPD pedals
- Dura-Ace chain
- System 4 seatpost and Vetta SL titanium saddle



## Model 9800

| Sizes                                          | 16.5     | 18   | 19.5                 | 21   |
|------------------------------------------------|----------|------|----------------------|------|
| 1. Stand-over height                           |          |      |                      |      |
| Inches                                         | 28.5     | 29.2 | 30.1                 | 31.5 |
| Centimeters                                    | 72.3     | 74.1 | 76.4                 | 79.9 |
| 2. Top tube                                    |          |      |                      |      |
| Inches                                         | 21.9     | 22.4 | 22.7                 | 22.9 |
| Centimeters                                    | 55.7     | 57.0 | 57.7                 | 58.2 |
| 3. Stem extension (Direct Connect, 7° drop)    |          |      |                      |      |
| Millimeters                                    | 120      | 135  | 135                  | 150  |
| 4. Reach (top tube + stem reach)               |          |      |                      |      |
| Inches                                         | 26.6     | 27.6 | 27.9                 | 28.7 |
| Centimeters                                    | 67.5     | 70.2 | 70.9                 | 73.0 |
| 5. Handlebar width (25.4 mm diameter, 5° bend) |          |      |                      |      |
| Millimeters                                    | 560      | 560  | 560                  | 560  |
| 6. Crank arm length                            |          |      |                      |      |
| Millimeters                                    | 175      | 175  | 175                  | 175  |
| 7. Steerer length, OS, non-threaded            |          |      |                      |      |
| Inches                                         | 7.6      | 7.6  | 8.1                  | 9.5  |
| Millimeters                                    | 192      | 192  | 205                  | 241  |
| 8. Head tube length                            |          |      |                      |      |
| Inches                                         | 4.3      | 4.3  | 4.8                  | 6.3  |
| Millimeters                                    | 110      | 110  | 123                  | 159  |
| 9. Seatpost length (27.2 mm diameter)          |          |      |                      |      |
| Millimeters                                    | 300      | 300  | 350                  | 350  |
| 10. Gearing                                    | 26/36/46 |      | 12-14-16-18-21-24-28 |      |

### General Information

|                  |                            |
|------------------|----------------------------|
| Hubset, Type     | HyperGlide                 |
| Spoke number     | 32                         |
| Spokes, Front    | 269 14/15ga.               |
| Rear(D/ND)       | 268/269 14/15ga.           |
| Tire Size        | 26 x 2.1                   |
| Front Derailleur | 34.9 mm/1 <sup>3/8</sup> " |
| Bottom bracket   | BB-UN71                    |
| Shell Width      | 73                         |
| Axle length      | 127.5                      |
| R. dropout width | 135 mm                     |
| Headset size     | 25.4/34.0/30.0             |
| Weight           | 25.3 lb/11.5 kg.           |

### Upgrades

- OCLV carbon fiber composite frame
- Trek Mogul Black Diamond fork
- Suspension with adjustable preload and damping
- Deore XT group with XT SPD pedals
- System 4 bars (130 gm), bar-ends, and seatpost

## Model 9900

| Sizes                                          | 16.5     | 18   | 19.5                    | 21   |
|------------------------------------------------|----------|------|-------------------------|------|
| 1. Stand-over height                           |          |      |                         |      |
| Inches                                         | 28.5     | 29.2 | 30.1                    | 31.5 |
| Centimeters                                    | 72.3     | 74.1 | 76.4                    | 79.9 |
| 2. Top tube                                    |          |      |                         |      |
| Inches                                         | 21.9     | 22.4 | 22.7                    | 22.9 |
| Centimeters                                    | 55.7     | 57.0 | 57.7                    | 58.2 |
| 3. Stem extension (Direct Connect, 7° drop)    |          |      |                         |      |
| Millimeters                                    | 120      | 135  | 135                     | 150  |
| 4. Reach (top tube + stem reach)               |          |      |                         |      |
| Inches                                         | 26.6     | 27.6 | 27.9                    | 28.7 |
| Centimeters                                    | 67.5     | 70.2 | 70.9                    | 73.0 |
| 5. Handlebar width (25.4 mm diameter, 5° bend) |          |      |                         |      |
| Millimeters                                    | 560      | 560  | 560                     | 560  |
| 6. Crank arm length                            |          |      |                         |      |
| Millimeters                                    | 175      | 175  | 175                     | 175  |
| 7. Steerer length, OS, non-threaded            |          |      |                         |      |
| Inches                                         | 7.6      | 7.6  | 8.1                     | 9.5  |
| Millimeters                                    | 192      | 192  | 205                     | 241  |
| 8. Head tube length                            |          |      |                         |      |
| Inches                                         | 4.3      | 4.3  | 4.8                     | 6.3  |
| Millimeters                                    | 110      | 110  | 123                     | 159  |
| 9. Seatpost length (27.2 mm diameter)          |          |      |                         |      |
| Millimeters                                    | 250      | 300  | 350                     | 350  |
| 10. Gearing                                    | 26/36/46 |      | 12-13-14-16-18-21-24-28 |      |

### General Information

|                  |                            |
|------------------|----------------------------|
| Hubset, Type     | HyperGlide                 |
| Spoke number     | 32                         |
| Spokes, Front    | 269 14/15ga.               |
| Rear(D/ND)       | 268/269 14/15ga.           |
| Tire Size        | 26 x 2.1                   |
| Front Derailleur | 34.9 mm/1 <sup>3/8</sup> " |
| Bottom bracket   | BB-UN91                    |
| Shell Width      | 73                         |
| Axle length      | 113                        |
| R. dropout width | 135 mm                     |
| Headset size     | 25.4/34.0/30.0             |
| Weight           | 24.5 lb/11.1 kg.           |

### Upgrades

- Shimano XTR group
- 8 speed cassette
- Vetta SL titanium saddle
- Dura-Ace chain
- Dia-Compe AheadSet S-series



# Tandems

## Model T50

Data listed for Captain / Stoker

| Sizes                                                          | 50x46      | 54x50                | 58x53     | 62x56     |
|----------------------------------------------------------------|------------|----------------------|-----------|-----------|
| 1. Stand-over height                                           |            |                      |           |           |
| Inches                                                         | 30.0/27.6  | 30.9/29.7            | 32.4/31.2 | 34.1/32.5 |
| Centimeters                                                    | 76.3/70.0  | 78.5/75.5            | 82.4/79.2 | 86.6/82.6 |
| 2. Top tube                                                    |            |                      |           |           |
| Inches                                                         | 21.3/26.0  | 21.5/27.2            | 22.2/28.0 | 23.0/28.7 |
| Centimeters                                                    | 54.0/66.0  | 54.5/69.0            | 56.5/71.0 | 58.5/73.0 |
| 3. Captain's stem extension (1 1/4 inch, 30° rise) Stoker stem | 130 mm/35° |                      |           |           |
| Millimeters                                                    | 120        | 120                  | 135       | 135       |
| 4. Reach (top tube + stem reach)                               |            |                      |           |           |
| Inches                                                         | 24.8/21.6  | 25.0/22.8            | 26.2/23.6 | 27.0/24.4 |
| Centimeters                                                    | 62.9/54.9  | 63.4/57.9            | 66.5/59.9 | 68.5/61.9 |
| 5. Handlebar width (25.4 mm diameter, 5° bend)                 |            |                      |           |           |
| Millimeters                                                    | 560/560    | 560/560              | 560/560   | 560/560   |
| 6. Crank arm length                                            |            |                      |           |           |
| Millimeters                                                    | 170/170    | 175/175              | 175/175   | 175/175   |
| 7. Steerer length, 1 1/4 inch, threaded                        |            |                      |           |           |
| Inches                                                         | 5.8        | 5.8                  | 7.3       | 9.2       |
| Millimeters                                                    | 148        | 148                  | 185       | 233       |
| 8. Head tube length                                            |            |                      |           |           |
| Inches                                                         | 4.0        | 4.0                  | 5.4       | 7.3       |
| Millimeters                                                    | 102        | 102                  | 137       | 185       |
| 9. Seatpost length (29.8 mm diameter)                          |            |                      |           |           |
| Millimeters                                                    | 350/300    | 350/300              | 350/350   | 350/350   |
| 10. Gearing                                                    | 28/38/48   | 12-14-16-19-22-26-30 |           |           |

## General Information

|                  |                                   |
|------------------|-----------------------------------|
| Hubset, Type     | cassette, threaded for drum brake |
| Spoke number     | 40R/36F                           |
| Spokes, Front    | 301 13/14ga.                      |
| Rear(D/ND)       | 296/296 13/14ga.                  |
| Tire Size        | 700x38                            |
| Front Derailleur | 28.6 mm/1 1/8"                    |
| Bottom brackets  | 3RRB                              |
| Shell Width      | 73                                |
| Axle length      | 42/52/42                          |
| R. dropout width | 140 mm                            |
| Headset size     | 29.2/37.8/33.6                    |
| Weight           | 42.1 lb/19.1kg.                   |

## Upgrades

- Custom gauge True Temper double butted Cro-Moly frame
- Special tandem wheelset with 40°R/36°F, 13/14 gauge stainless steel spokes, Titan Tour rims
- Deore DX derailleurs and shifters
- M System cantilever brakes
- System 2 Gel Lite saddles



## Model T100

Data listed for Captain / Stoker

| Sizes                                                                     | 50x46     | 54x50                | 58x53     | 62x56     |
|---------------------------------------------------------------------------|-----------|----------------------|-----------|-----------|
| 1. Stand-over height                                                      |           |                      |           |           |
| Inches                                                                    | 30.0/27.6 | 30.9/29.7            | 32.4/31.2 | 34.1/32.5 |
| Centimeters                                                               | 76.3/70.0 | 78.5/75.5            | 82.4/79.2 | 86.6/82.6 |
| 2. Top tube                                                               |           |                      |           |           |
| Inches                                                                    | 21.3/26.0 | 21.5/27.2            | 22.2/28.0 | 23.0/28.7 |
| Centimeters                                                               | 54.0/66.0 | 54.5/69.0            | 56.5/71.0 | 58.5/73.0 |
| 3. Captain's stem extension (1 1/4 inch, 30° rise) Stoker stem 130 mm/35° |           |                      |           |           |
| Millimeters                                                               | 120       | 120                  | 135       | 150       |
| 4. Reach (top tube + stem reach)                                          |           |                      |           |           |
| Inches                                                                    | 24.8/21.6 | 25.4/22.8            | 26.2/23.6 | 27.4/24.4 |
| Centimeters                                                               | 62.9/54.9 | 64.4/57.9            | 66.5/59.9 | 69.7/61.9 |
| 5. Handlebar width (25.4 mm diameter)                                     |           |                      |           |           |
| Millimeters                                                               | 560/560   | 560/560              | 560/560   | 560/560   |
| 6. Crank arm length                                                       |           |                      |           |           |
| Millimeters                                                               | 175/175   | 175/175              | 175/175   | 175/175   |
| 7. Steerer length, 1 1/4 inch, threaded                                   |           |                      |           |           |
| Inches                                                                    | 5.8       | 5.8                  | 7.3       | 9.2       |
| Millimeters                                                               | 148       | 148                  | 185       | 233       |
| 8. Head tube length                                                       |           |                      |           |           |
| Inches                                                                    | 4.0       | 4.0                  | 5.4       | 7.3       |
| Millimeters                                                               | 102       | 102                  | 137       | 185       |
| 9. Seatpost length (29.8 mm diameter)                                     |           |                      |           |           |
| Millimeters                                                               | 350/300   | 350/300              | 350/350   | 350/350   |
| 10. Gearing                                                               | 28/38/48  | 12-14-16-19-21-24-28 |           |           |

### General Information

|                  |                  |
|------------------|------------------|
| Hubset, Type     | HyperGlide       |
| Spoke number     | 40R/36F          |
| Spokes, Front    | 296 13/14ga.     |
| Rear(D/ND)       | 298/299 13/14ga. |
| Tire Size        | 700x35           |
| Front Derailleur | 28.6 mm/1 1/8"   |
| Bottom brackets  | BB-UN51          |
| Shell Width      | 68               |
| Axle length      | 127.5            |
| R. dropout width | 140              |
| Headset size     | 29.2/37.8/33.6   |
| Weight           | 42.1 lb/19.1 kg. |

### Upgrades

- Full Shimano Deore DX group
- Custom 140 mm, 40/36° cassette hubset
- RapidFire Plus shifting
- System 2 pedals, bars (170 gm)
- Trek Invert K 700x35 tires with Kevlar belts
- Road conversion easily performed

## Model T200

Data listed for Captain / Stoker

| Sizes                                                              | 50x46      | 54x50                   | 58x53      | 62x56      |
|--------------------------------------------------------------------|------------|-------------------------|------------|------------|
| 1. Stand-over height                                               |            |                         |            |            |
| Inches                                                             | 30.0/27.6  | 30.9/29.7               | 32.4/31.2  | 34.1/32.5  |
| Centimeters                                                        | 76.3/70.0  | 78.5/75.5               | 82.4/79.2  | 86.6/82.6  |
| 2. Top tube                                                        |            |                         |            |            |
| Inches                                                             | 21.3/26.0  | 21.5/27.2               | 22.2/28.0  | 23.0/28.7  |
| Centimeters                                                        | 54.0/66.0  | 54.5/69.0               | 56.5/71.0  | 58.5/73.0  |
| 3. Captain's stem extension (1 1/4 inch, 0° rise) Stoker stem adj. |            |                         |            |            |
| Millimeters                                                        | 100        | 100                     | 120        | 120        |
| 4. Reach (top tube + stem reach)                                   |            |                         |            |            |
| Inches                                                             | 25.2/22-20 | 25.4/23-21              | 27.0/24-22 | 27.8/24-22 |
| Centimeters                                                        | 64.0/57-52 | 64.5/60-55              | 68.5/62-57 | 70.5/64-59 |
| 5. Handlebar width (25.4 mm diameter)                              |            |                         |            |            |
| Millimeters                                                        | 420/460    | 420/460                 | 440/460    | 440/460    |
| 6. Crank arm length                                                |            |                         |            |            |
| Millimeters                                                        | 170/170    | 170/170                 | 175/170    | 175/175    |
| 7. Steerer Length, 1 1/4 inch, threaded                            |            |                         |            |            |
| Inches                                                             | 5.8        | 5.8                     | 7.3        | 9.2        |
| Millimeters                                                        | 148        | 148                     | 185        | 233        |
| 8. Head tube length                                                |            |                         |            |            |
| Inches                                                             | 4.0        | 4.0                     | 5.4        | 7.3        |
| Millimeters                                                        | 102        | 102                     | 137        | 185        |
| 9. Seatpost length (29.8 mm diameter)                              |            |                         |            |            |
| Millimeters                                                        | 350/300    | 350/300                 | 350/350    | 350/350    |
| 10. Gearing                                                        | 32/44/54   | 12-13-14-16-18-21-24-28 |            |            |

### General Information

|                  |                                   |
|------------------|-----------------------------------|
| Hubset, Type     | cassette, threaded for drum brake |
| Spoke number     | 40R/36F                           |
| Spokes, Front    | 297 13/14ga.                      |
| Rear(D/ND)       | 297/298 13/14ga.                  |
| Tire Size        | 700x28                            |
| Front Derailleur | 28.6 mm/1 1/8"                    |
| Bottom brackets  | BB-UN71                           |
| Shell Width      | 68                                |
| Axle length      | 127.5                             |
| R. dropout width | 140 mm                            |
| Headset size     | 29.2/37.8/33.6                    |
| Weight           | 41.8 lb/19.0 kg.                  |

### Upgrades

- XTR brakes and derailleurs
- Hugi 8 speed hubs with XTR cassette, threaded for drum brake
- Matrix Journey rims with Iso Tech 3K tires with Kevlar belts
- System 3 adjustable stoker stem
- System 3 wide racing saddles with leather covers and hollow Cro-Moly rails



# Jazz

## Latitude

| Sizes                                 | 14.5     | 16.5 | 18   | 20             | 22   | 17W | 20W |
|---------------------------------------|----------|------|------|----------------|------|-----|-----|
| 1. Stand-over height                  |          |      |      |                |      |     |     |
| Inches                                | 27.4     | 28.5 | 29.2 | 30.6           | 33.7 |     |     |
| Centimeters                           | 69.7     | 72.4 | 74.2 | 77.8           | 84.5 |     |     |
| 2. Top tube                           |          |      |      |                |      |     |     |
| Inches                                | 20.9     | 21.7 | 22.3 | 22.6           | 23   |     |     |
| Centimeters                           | 53       | 55   | 56.6 | 57.4           | 58.4 |     |     |
| 3. Stem extension (45° rise)          |          |      |      |                |      |     |     |
| Millimeters                           | 100      | 100  | 100  | 100            | 100  | 100 | 100 |
| 4. Reach (top tube + stem reach)      |          |      |      |                |      |     |     |
| Inches                                | 22.6     | 23.4 | 24.0 | 24.4           | 24.9 |     |     |
| Centimeters                           | 57.5     | 59.5 | 61.1 | 61.9           | 63.3 |     |     |
| 5. Handlebar width (25.4 mm diameter) |          |      |      |                |      |     |     |
| Centimeters                           | 580      | 580  | 580  | 580            | 580  | 600 | 600 |
| 6. Crank Arm length                   |          |      |      |                |      |     |     |
| Inches                                | 6.5      | 6.5  | 6.5  | 6.5            | 6.5  | 6.5 | 6.5 |
| 7. Steerer length, threaded           |          |      |      |                |      |     |     |
| Inches                                | 4.9      | 4.9  | 4.9  | 6.1            | 8.0  | 6.5 | 7.6 |
| Millimeters                           | 124      | 124  | 124  | 154            | 204  | 164 | 194 |
| 8. Head tube length                   |          |      |      |                |      |     |     |
| Inches                                | 3.3      | 3.3  | 3.3  | 4.5            | 6.5  | 4.9 | 6.1 |
| Millimeters                           | 85       | 85   | 85   | 115            | 165  | 125 | 155 |
| 9. Seatpost length (26.2 diameter)    |          |      |      |                |      |     |     |
| Millimeters                           | 300      | 300  | 300  | 300            | 300  | 300 | 300 |
| 10. Gearing                           | 28/38/48 |      |      | 14-17-20-24-28 |      |     |     |

### General Information

|                  |                            |
|------------------|----------------------------|
| Hubset, Type     | Freewheel, natted          |
| Spoke number     | 36                         |
| Spokes, Front    | 261 14 ga.                 |
| Rear(D/ND)       | 259/261 14 ga.             |
| Tire Size        | 26x2.1                     |
| Front Derailleur | 28.6 mm/1 <sup>1/8</sup> " |
| Bottom bracket   | One-piece type             |
| R. dropout width | 130                        |
| Headset size     | 22.2/30.0/27.0             |

### Upgrades

- 15 speeds
- Dia-Compe brakes
- Hi-density foam saddle
- Hi-rise stem and handlebars

## Voltage

| Sizes                                 | 14.5     | 16.5 | 18   | 20                 | 22   | 17W | 20W |
|---------------------------------------|----------|------|------|--------------------|------|-----|-----|
| 1. Stand-over height                  |          |      |      |                    |      |     |     |
| Inches                                | 27.4     | 28.5 | 29.2 | 30.6               | 33.7 | NA  | NA  |
| Centimeters                           | 69.7     | 72.4 | 74.2 | 77.8               | 84.5 |     |     |
| 2. Top tube                           |          |      |      |                    |      |     |     |
| Inches                                | 20.9     | 21.7 | 22.3 | 22.6               | 23   |     |     |
| Centimeters                           | 53       | 55   | 56.6 | 57.4               | 58.4 |     |     |
| 3. Stem extension (45° rise)          |          |      |      |                    |      |     |     |
| Millimeters                           | 100      | 100  | 100  | 100                | 100  | 100 | 100 |
| 4. Reach (top tube + stem reach)      |          |      |      |                    |      |     |     |
| Inches                                | 22.6     | 23.4 | 24.0 | 24.4               | 24.9 |     |     |
| Centimeters                           | 57.5     | 59.5 | 61.1 | 61.9               | 63.3 |     |     |
| 5. Handlebar width (25.4 mm diameter) |          |      |      |                    |      |     |     |
| Centimeters                           | 580      | 580  | 580  | 580                | 580  | 600 | 600 |
| 6. Crank Arm length                   |          |      |      |                    |      |     |     |
| Millimeters                           | 170      | 2170 | 170  | 170                | 170  | 170 | 170 |
| 7. Steerer length, threaded           |          |      |      |                    |      |     |     |
| Inches                                | 4.9      | 4.9  | 4.9  | 6.1                | 8.0  | 6.5 | 7.6 |
| Millimeters                           | 124      | 124  | 124  | 154                | 204  | 164 | 194 |
| 8. Head tube length                   |          |      |      |                    |      |     |     |
| Inches                                | 3.3      | 3.3  | 3.3  | 4.5                | 6.5  | 4.9 | 6.1 |
| Millimeters                           | 85       | 85   | 85   | 115                | 165  | 125 | 155 |
| 9. Seatpost length (26.2 diameter)    |          |      |      |                    |      |     |     |
| Millimeters                           | 300      | 300  | 300  | 300                | 300  | 300 | 300 |
| 10. Gearing                           | 28/38/48 |      |      | 14-16--18-21-24-28 |      |     |     |

### General Information

|                  |                            |
|------------------|----------------------------|
| Hubset, Type     | Freewheel w/QR             |
| Spoke number     | 36                         |
| Spokes, Front    | 264 14 ga.                 |
| Rear(D/ND)       | 261/263 14 ga.             |
| Tire Size        | 26x2.1                     |
| Front Derailleur | 28.6 mm/1 <sup>1/8</sup> " |
| Bottom bracket   | BB-CS11                    |
| Shell Width      | 68                         |
| Axle length      | 122.5                      |
| R. dropout width | 130                        |
| Headset size     | 22.2/30.0/27.0             |

### Upgrades

- Three piece crank
- Cartridge bottom bracket
- M-System brakes
- 18 speeds
- Alloy rims
- Quick release wheels, front and rear



## Street Life

| Sizes                                 | 17   | 19                | 21   | 23   | 17W | 20W |
|---------------------------------------|------|-------------------|------|------|-----|-----|
| 1. Stand-over height                  |      |                   |      |      |     |     |
| Inches                                | 27.6 | 29.5              | 31.4 | 33.3 |     |     |
| Centimeters                           | 70.2 | 75.0              | 79.8 | 84.6 |     |     |
| 2. Top tube                           |      |                   |      |      |     |     |
| Inches                                | 21.3 | 21.9              | 22.2 | 22.6 |     |     |
| Centimeters                           | 54.0 | 55.5              | 56.5 | 57.5 |     |     |
| 3. Stem extension (45° rise)          |      |                   |      |      |     |     |
| Millimeters                           | 100  | 100               | 100  | 100  | 100 | 100 |
| 4. Reach (top tube + stem reach)      |      |                   |      |      |     |     |
| Inches                                | 23.0 | 23.6              | 24.0 | 24.4 |     |     |
| Centimeters                           | 58.5 | 60.0              | 61.0 | 62.0 |     |     |
| 5. Handlebar width (25.4 mm diameter) |      |                   |      |      |     |     |
| Millimeters                           | 600  | 600               | 600  | 600  | 600 | 600 |
| 6. Crank Arm length                   |      |                   |      |      |     |     |
| Millimeters                           | 170  | 170               | 170  | 170  | 170 | 170 |
| 7. Steerer length, non-threaded       |      |                   |      |      |     |     |
| Inches                                | 4.9  | 5.3               | 6.1  | 8.0  | 6.5 | 7.6 |
| Millimeters                           | 124  | 134               | 154  | 204  | 164 | 194 |
| 8. Head tube length                   |      |                   |      |      |     |     |
| Inches                                | 3.3  | 3.7               | 4.5  | 6.5  | 4.9 | 6.5 |
| Millimeters                           | 85   | 95                | 115  | 165  | 125 | 165 |
| 9. Seatpost length (26.2 diameter)    |      |                   |      |      |     |     |
| Millimeters                           | 300  | 300               | 300  | 300  | 300 | 300 |
| 10. Gearing                           | 48   | 14-16-18-21-24-28 |      |      |     |     |

## General Information

|                  |                   |
|------------------|-------------------|
| Hubset, Type     | Freewheel, natted |
| Spoke number     | 36                |
| Spokes, Front    | 297 14 ga.        |
| Rear(D/ND)       | 294/296 14 ga.    |
| Tire Size        | 700x35            |
| Front Derailleur | 28.6 mm / 1 1/8"  |
| Bottom bracket   | 3A 32/52/33.5     |
| Shell Width      | 68                |
| Axle length      | 117.5             |
| R. dropout width | 128               |
| Headset size     | 22.2/30.0/27.0    |

## Calypso

|                                    |                          |
|------------------------------------|--------------------------|
| 1. Stand-over height               | 30.75" / 78.1 cm (men's) |
| 2. Crank Arm length                | 6.5" / 165 mm            |
| 3. Handlebar width                 | 700 mm                   |
| 4. Steerer length                  | 144 mm                   |
| 5. Head tube length                | 105 mm                   |
| 6. Seatpost length (25.4 diameter) | 300 mm                   |
| 7. Gearing                         | 40 14-16-18-21-24-28     |
| 8. Hubset, Type                    | Bolt on, freewheel       |
| Spoke number                       | 36                       |
| 9. Spokes, front                   | 263                      |
| rear                               | 263                      |
| 10. Tire size                      | 26x2.125                 |
| 11. Bottom bracket                 | One piece                |
| 12. R. dropout width               | 130 mm                   |
| 13. Headset size                   | 22.2/32.5/27.0           |

## Cruiser Classic

|                                    |                        |
|------------------------------------|------------------------|
| 1. Stand-over height               | 30.75"/78.1 cm (men's) |
| 2. Crank Arm length                | 6.5"/165 mm            |
| 3. Handlebar width                 | 700 mm                 |
| 4. Steerer length                  | 144 mm                 |
| 5. Head tube length                | 105 mm                 |
| 6. Seatpost length (25.4 diameter) | 300 mm                 |
| 7. Gearing                         | 40 x 18                |
| 8. Hubset, Type                    | Coaster                |
| Spoke number                       | 36                     |
| 9. Spokes, front                   | 263                    |
| rear                               | 260                    |
| 10. Tire size                      | 26x2.125               |
| 11. Bottom bracket                 | One piece              |
| 12. R. dropout width               | 110 mm                 |
| 13. Headset size                   | 22.2/32.5/27.0         |



## Cherry Bomb

|                                    |                         |
|------------------------------------|-------------------------|
| 1. Stand-over height               | 27"/68.6 cm             |
| 2. Crank Arm length                | 6.5 "/165 mm            |
| 3. Handlebar width                 | 560 mm                  |
| 4. Steerer length                  | 144 mm                  |
| 5. Head tube length                | 105 mm                  |
| 6. Seatpost length (5/8" diameter) | 300 mm                  |
| 7. Gearing                         | 28/38/48 14-17-20-24-28 |
| 8. Hubset, Type                    | Bolt on, freewheel      |
| Spoke number                       | 36                      |
| 9. Spokes, front                   | 240                     |
| rear (D/ND)                        | 237/239                 |
| 10. Tire size                      | 24x2.1                  |
| 11. Bottom bracket                 | One piece               |
| 12. R. dropout width               | 130 mm                  |
| 13. Headset size                   | 22.2/30.0/27.0          |

## Rocket

|                                    |                         |
|------------------------------------|-------------------------|
| 1. Stand-over height               | 27"/68.6 cm             |
| 2. Crank Arm length                | 5.5 " / 140 mm          |
| 3. Handlebar width                 | 560 mm                  |
| 4. Steerer length                  | 144 mm                  |
| 5. Head tube length                | 105 mm                  |
| 6. Seatpost length (5/8" diameter) | 300 mm                  |
| 7. Gearing                         | 26/36/46 14-17-20-24-28 |
| 8. Hubset, Type                    | Bolt on, freewheel      |
| Spoke number                       | 36                      |
| 9. Spokes, front                   | 237                     |
| rear (D/ND)                        | 234/236                 |
| 10. Tire size                      | 24x2.1                  |
| 11. Bottom bracket                 | One piece               |
| 12. R. dropout width               | 130 mm                  |
| 13. Headset size                   | 22.2/30.0/27.0          |

## Bold Moves

|                                    |                          |
|------------------------------------|--------------------------|
| 1. Stand-over height               | 23"/58.4 cm              |
| 2. Crank Arm length                | 5.5 "/140 mm             |
| 3. Handlebar width                 | 560 mm                   |
| 4. Steerer length                  | 134 mm boys/154 mm girls |
| 5. Head tube length                | 95 mm boys/115 mm girls  |
| 6. Seatpost length (5/8" diameter) | 300 mm                   |
| 7. Gearing                         | 44x14-17-20-24-28        |
| 8. Hubset, Type                    | Bolt on, freewheel       |
| Spoke number                       | 36                       |
| 9. Spokes, front                   | 190                      |
| rear (D/ND)                        | 186/188                  |
| 10. Tire size                      | 20x2.0                   |
| 11. Bottom bracket                 | One piece                |
| 12. R. dropout width               | 126 mm                   |
| 13. Headset size                   | 22.2/30.0/27.0           |

## X-IT

|                                    |                              |
|------------------------------------|------------------------------|
| 1. Stand-over height               | 23.5"/60 cm                  |
| 2. Crank Arm length                | 6.5"/165 mm                  |
| 3. Handlebar width                 | 620 mm                       |
| 4. Steerer length                  | 142 mm                       |
| 5. Head tube length                | 102 mm                       |
| 6. Seatpost length (26.2 diameter) | 300 mm                       |
| 7. Gearing                         | 44x16T (18T coaster)         |
| 8. Hubset, Type                    | Coaster, or nutted freewheel |
| Spoke number                       | 36                           |
| 9. Spokes, front                   | 190                          |
| rear                               | 188 (186- coaster)           |
| 10. Tire size                      | 20x2.125                     |
| 11. Bottom bracket                 | One piece                    |
| 12. R. dropout width               | 112 mm                       |
| 13. Headset size                   | 21.2/32.5/27.0               |



## *Zig Zag*

|                                    |                    |
|------------------------------------|--------------------|
| 1. Stand-over height               | 22"/55.4 cm (boys) |
| 2. Crank Arm length                | 4.5 "/114 mm       |
| 3. Handlebar width                 | 170 mm             |
| 4. Steerer length                  | 130 mm             |
| 5. Head tube length                | 90 mm              |
| 6. Seatpost length (26.2 diameter) | 250 mm             |
| 7. Gearing                         | 36x18T             |
| 8. Hubset, Type                    | Coaster            |
| Spoke number                       | 36                 |
| 9. Spokes, front                   | 185                |
| rear                               | 183                |
| 10. Tire size                      | 20x2.125           |
| 11. Bottom bracket                 | One piece          |
| 12. R. dropout width               | 112 mm             |
| 13. Headset size                   | 21.2/32.5/27.0     |

## *Wizard*

|                                    |                       |
|------------------------------------|-----------------------|
| 1. Stand-over height               | 19.25"/48.9 cm (boys) |
| 2. Crank Arm length                | 4.5"/114 mm           |
| 3. Handlebar width                 | 130 mm                |
| 4. Steerer length                  | 139 mm                |
| 5. Head tube length                | 102 mm                |
| 6. Seatpost length (26.2 diameter) | 220 mm                |
| 7. Gearing                         | 32x16T                |
| 8. Hubset, Type                    | Coaster               |
| Spoke number                       | 28                    |
| 9. Spokes, front                   | 137                   |
| rear                               | 132                   |
| 10. Tire size                      | 16x1.75               |
| 11. Bottom bracket                 | One piece             |
| 12. R. dropout width               | 112 mm                |
| 13. Headset size                   | 21.2/32.5/27.0        |